



SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION					
Product:	PENTREAT™ 244-20 W/B		Part Number: 3473000		
Manufacturer:	W. R. MEADOWS, INC.		Address: 300 Industrial Drive Hampshire, Illinois 60140		
Telephone:	(847) 214-2100		In case of emergency, dial (800) 424-9300 (CHEMTREC)		
Revision Date:	1/13/2022				
Product Use:	Penetrating Concrete Sealer				
SECTION 2: HAZARDS IDENTIFICATION/EXPOSURE LIMITS					
HMIS		HAZARD STATEMENTS			
[Health]	1	WARNING!			
[Flammability]	2	Flammable liquid/vapor. (Category 4)			
[Reactivity]	0	Causes skin irritation. (Category 2)			
[Personal Protection]		Causes serious eye damage. (Category 1) Harmful if inhaled. (Category 4)			
		PRECAUTIONARY STATEMENTS			
		Use appropriate personal protective equipment.			
		Keep away from ignition sources.			
		Avoid direct contact/inhalation of aerosols/vapors.			
					
SECTION 3: HAZARDS COMPONENTS					
Chemical Name:	CAS Number	% by Weight	SARA 313	Vapor Pressure (mm Hg@20°C)	LEL (@25°C)
1. Organic Siloxane.	102782-92-3	1-5	No	N/E	N/E
2. Glycol Ether	9043-30-5	1-5	No	N/E	N/E
3. Polydimethylsiloxane	75718-16-0	1-5	No	N/E	N/E
Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1966 (SARA) and 40 CFR Part 372, chemicals listed on the 313 List (40 CFR Part 373.65) are identified under the heading "SARA 313."					
SECTION 4: EMERGENCY AND FIRST AID PROCEDURES					
EYE CONTACT: Immediately flush eyes with water for fifteen (15) minutes. If symptoms persist, seek medical attention.					
SKIN CONTACT: Remove contaminated shoes/clothing. Wipe excess from skin and flush with water for fifteen (15) minutes. If symptoms persist, seek medical attention. Do not reuse clothing until thoroughly decontaminated.					
INHALATION: If symptoms develop move victim from exposure source and into fresh air. Treat symptomatically.					
INGESTION: Not anticipated to be an exposure route. If ingested and vomiting occurs keep the victims head below the hips to prevent lung aspiration. Do not induce vomiting. Seek immediate medical attention.					
MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND CHRONIC: See Section Eleven for Symptoms/Effects.					
SECTION 5: FIRE AND EXPLOSIVES HAZARDS					
FLASHPOINT: 158°F					
EXTINGUISHING MEDIA: Alcohol-resistant foam, dry chemical or carbon dioxide.					
CHEMICAL/COMBUSTION HAZARDS: Hazardous combustion products include carbon dioxide, carbon monoxide, silicon dioxide and incomplete combustion products.					
PRECAUTIONS/PERSONAL PROTECTIVE EQUIPMENT: This product will flash but does not sustain combustion. As a result of hydrolysis, flammable vapors may accumulate in container head space. Consider possible formation of explosive mixtures with air, for example, in uncleaned containers by moisture. Explosion limits for hydrolysis product 3.5-15% v/v (ethanol).					
SECTION 6: ACCIDENTAL RELEASE MEASURES					
SPILL OR LEAK PROCEDURES: Dike and contain. Utilize appropriate personal protective equipment. Recover free product and absorb residues with an appropriate absorbent. Place in non-leaking marked containers for disposal. Eliminate all ignition sources.					
SECTION 7: HANDLING AND STORAGE					
SAFE HANDLING PROCEDURES: Avoid direct contact.					
SAFE STORAGE: Keep containers closed when not in use. Protect product from moisture contamination.					

SAFETY DATA SHEET

Date of Preparation: 1/13/22		Page 2 of 3			3473000			
SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION								
	OSHA				ACGIH			
Chemical Name:	PEL	PEL/CEILING	PEL/STEL	SKIN	TWA	TLV/CEILING	TLV/STEL	SKIN
1. Organic Siloxane	N/E	N/E	N/E	N/E	N/E	N/E	N/E	N/E
2. Glycol Ether	N/E	N/E	N/E	N/E	N/E	N/E	N/E	N/E
3. Polydimethylsiloxane	N/E	N/E	N/E	N/E	N/E	N/E	N/E	N/E
<i>N/E = Not Established</i>								
ENGINEERING CONTROLS: Local ventilation may be required at point of use.								
PERSONAL PROTECTIVE EQUIPMENT: Safety glasses, chemical-resistant gloves.								
SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES								
BOILING POINT: N/E			VAPOR DENSITY: N/A			% VOLATILE BY VOLUME: N/E		
EVAPORATION RATE: <1 (Ether=1)			pH LEVEL: N/A			% VOLATILE BY WEIGHT: N/E		
WEIGHT PER GALLON: 8.15			PRODUCT APPEARANCE: Milky white liquid			VOC CONTENT: <350 g/L		
ODOR: Mild Organic			ODOR THRESHOLD: N/D			MELTING/FREEZING POINT: N/D		
FLAMMABILITY: N/D			UEL/LEL: N/D			VAPOR PRESSURE: N/D		
RELATIVE DENSITY: N/D			SOLUBILITY: N/D			PARTITION COEFFICIENT: N/D		
AUTOIGNITION TEMPERATURE: N/D			DECOMPOSITION TEMPERATURE: N/D			VISCOSITY: N/D		
<i>N/A = Not Applicable N/D = Not Determined N/E = Not Established</i>								
SECTION 10: STABILITY/REACTIVITY								
STABILITY: Stable.			HAZARDOUS POLYMERIZATION: Will not occur.					
CONDITIONS AND MATERIALS TO AVOID: Moisture, acids, and bases.								
HAZARDOUS DECOMPOSITION PRODUCTS: Ethanol and Methanol								
SECTION 11: TOXICOLOGICAL INFORMATION								
EYE CONTACT: Direct contact may cause mild to moderate irritation.								
SKIN CONTACT: Direct contact may cause mild irritation. Prolonged contact may also cause irritation.								
INHALATION: Not anticipated to be an exposure route. Exposure to aerosols/mists may irritate the respiratory tract.								
INGESTION: Not expected to be an exposure route. Ingestion may cause irritation of the digestive tract.								
SIGNS AND SYMPTOMS: Symptoms of eye irritation include pain, tearing, redness, and swelling. Symptoms of skin irritation include rash, redness and swelling. Respiratory irritation symptoms include runny nose, sore throat, coughing, chest discomfort, shortness of breath, and reduced lung function. Symptoms of gastrointestinal irritation include sore throat, nausea, abdominal pain, vomiting, and diarrhea.								
AGGRAVATED MEDICAL CONDITIONS: Pre-existing skin, eye, and respiratory disorders may be aggravated by product exposure.								
OTHER HEALTH EFFECTS: None recognized.								
SECTION 12: ECOLOGICAL INFORMATION								
ECOTOXICITY: N/E			DEGRADABILITY: N/E			BIOACCUMULATIVE POTENTIAL: N/E		
SOIL MOBILITY: N/E			OTHER ADVERSE EFFECTS: N/E			<i>N/E = Not Established</i>		
SECTION 13: WASTE DISPOSAL INFORMATION								
WASTE DISPOSAL INFORMATION: Hazardous waste (D001). Disposal by fuel blending or incineration is recommended.								
SECTION 14: TRANSPORTATION INFORMATION								
HAZARDOUS/NON-HAZARDOUS MATERIAL: Non-hazardous.								
UN NUMBER: None.			HAZARD CLASS: None.			PACKING GROUP: None.		
UN PROPER SHIPPING NAME: N/E								
ENVIRONMENTAL HAZARDS: None recognized.								
BULK TRANSPORTATION INFORMATION: Not applicable. Product not shipped in bulk configuration.								
SPECIAL PRECAUTIONS: None						<i>N/E: Not Established</i>		
SECTION 15: REGULATORY INFORMATION								
OTHER REGULATORY CONSIDERATIONS: None.								

SAFETY DATA SHEET

Date of Preparation: 1/13/22	Page 3 of 3	3473000
SECTION 16: OTHER INFORMATION		
PREPARATION DATE:	1/13/2022	
PREPARED BY:	Dave Carey	

The information contained herein is based on the data available to us and is believed to be correct. However, we make no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injury from the use of this product described herein.

UNITIS
CONTRACTOR SUPPLIES