




# DETECTABLE WARNING ADA PAVERS



A-10



A-20



A-30



A-40  
Federal Yellow  
33538



A-50




A-60




A-70




A-80



A-90



A-100



A-110



A-120


Due to the natural variances in aggregate materials, the color characteristics of manufactured pavers may differ slightly from the color swatches pictured. Your monitor or printer may not be an accurate representation of the actual production color or finish.

In compliance with the American with Disabilities Act and California Title 24.

PROPERTY	ADVANCED TESTING VALUE	TEST METHOD
Compressive Strength	> 8,000 PSI avg. with no individual unit less than 7,500 PSI	ASTM C 140
Water Absorption	< 6%	ASTM C 140
Flexural Strength	> 1,200 pounds average	ASTM C 140
Freeze/Thaw	< 1% loss of dry weight (100 cycles)	ASTM C 1262
Center Load	1,850 lbs.	WTCL 99

Testing based on 24"x24"x2" pressed paver

## ADA PATTERNS



ADA-2



TACTILE  
WARNING



DIRECTIONAL  
BAR

## STANDARD SIZES

All pavers available in thickness ranging from 2" - 2 3/4".

Directional Bar pattern only available in 12" x 12" sizing.

Check WausauTile.com or call your sales rep for more details.



24" sq.



12" sq.

**CALL FOR FURTHER DETAILS & PRICING.**

P: 800.388.8728 | E: wtile@wausautile.com | WAUSAUTILE.COM

Nov 2021