

SAFETY DATA SHEET

Sikaflex NP 1 white Formerly MSeal NP 1 White



Version 1.4 Revision Date: 02/02/2022 SDS Number: 000000641358 Date of last issue: 01/05/2021
 Date of first issue: 04/27/2020

SECTION 1. IDENTIFICATION

Product name : Sikaflex NP 1 white Formerly MSeal NP 1 White
 Product code : 00000000050426609

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC
 Address : 201 POLITO AVE
 Lyndhurst NJ 07071
 Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Sealant
 Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation : Category 2A
 Carcinogenicity : Category 2
 Specific target organ toxicity - repeated exposure : Category 1 (Central nervous system)
 Acute toxicity (Inhalation - vapour) : Category 4
 Respiratory sensitization : Category 1
 Skin sensitization : Category 1

GHS label elements

Hazard pictograms :

Signal Word : Danger

Hazard Statements : H319 Causes serious eye irritation.

SAFETY DATA SHEET

Sikaflex NP 1 white Formerly MSeal NP 1 White



Version 1.4	Revision Date: 02/02/2022	SDS Number: 000000641358	Date of last issue: 01/05/2021 Date of first issue: 04/27/2020
----------------	------------------------------	-----------------------------	---

H332 Harmful if inhaled.
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H317 May cause an allergic skin reaction.
 H351 Suspected of causing cancer.
 H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Precautionary Statements :

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P271 Use only outdoors or in a well-ventilated area.
 P260 Do not breathe dusts or mists.
 P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P284 In case of inadequate ventilation wear respiratory protection.
 P270 Do not eat, drink or smoke when using this product.
 P264 Wash face, hands and any exposed skin thoroughly after handling.
 P272 Contaminated work clothing should not be allowed out of the workplace.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P314 Get medical advice/ attention if you feel unwell.
 P302 + P352 IF ON SKIN: Wash with plenty of water.
 P362 + P364 Take off contaminated clothing and wash it before reuse.
 P337 + P313 If eye irritation persists: Get medical advice/ attention.
 P310 Immediately call a POISON CENTER or doctor/ physician.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

CONTAINS ISOCYANATES. INHALATION OF ISOCYANATE MISTS OR VAPORS MAY CAUSE RESPIRATORY IRRITATION, BREATHESSNESS, CHEST DISCOMFORT AND REDUCED PULMONARY FUNCTION. OVEREXPOSURE WELL ABOVE THE PEL MAY RESULT IN BRONCHITIS, BRONCHIAL SPASMS AND PULMONARY EDEMA. LONG-TERM EXPOSURE TO ISOCYANATES HAS BEEN REPORTED TO CAUSE LUNG DAMAGE, INCLUDING REDUCED LUNG FUNCTION WHICH MAY BE PERMANENT. ACUTE OR CHRONIC OVEREXPOSURE TO ISOCYANATES MAY CAUSE SENSITIZATION IN SOME

SAFETY DATA SHEET

Sikaflex NP 1 white Formerly MSeal NP 1 White



Version 1.4 Revision Date: 02/02/2022 SDS Number: 000000641358 Date of last issue: 01/05/2021
 Date of first issue: 04/27/2020

INDIVIDUALS, RESULTING IN ALLERGIC RESPIRATORY REACTIONS INCLUDING WHEEZING, SHORTNESS OF BREATH AND DIFFICULTY BREATHING. ANIMAL TESTS INDICATE THAT SKIN CONTACT MAY PLAY A ROLE IN CAUSING RESPIRATORY SENSITIZATION.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Polymer

Components

Chemical name	CAS-No.	Concentration (% w/w)
Limestone	1317-65-3	>= 15 - < 20
Titanium dioxide	13463-67-7	>= 3 - < 5
talc	14807-96-6	>= 3 - < 5
calcium oxide	1305-78-8	>= 1 - < 3
Stoddard solvent	8052-41-3	>= 1 - < 3
Bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexan-1,2-diylbiscarbamate	59719-67-4	>= 1 - < 3
toluene-2,6-diisocyanate	91-08-7	>= 0.4 - < 0.5
trimethoxy(3-(oxiranylmethoxy)propyl)silane	2530-83-8	>= 0.3 - < 1

SECTION 4. FIRST AID MEASURES

- General advice : First aid personnel should pay attention to their own safety. Remove contaminated clothing.
- If inhaled : Remove the affected individual into fresh air and keep the person calm. If breathing difficulties develop, aid in breathing and seek immediate medical attention.
- In case of skin contact : Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.
- In case of eye contact : In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. Remove contact lenses. Immediate medical attention required.
- If swallowed : Rinse mouth and then drink 200-300 ml of water. Do NOT induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediate medical attention required.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled.

SAFETY DATA SHEET

Sikaflex NP 1 white Formerly MSeal NP 1 White



Version 1.4	Revision Date: 02/02/2022	SDS Number: 000000641358	Date of last issue: 01/05/2021 Date of first issue: 04/27/2020
----------------	------------------------------	-----------------------------	---

May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Suspected of causing cancer.
Causes damage to organs through prolonged or repeated exposure.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam
Water spray
Dry powder
Carbon dioxide (CO2)

Unsuitable extinguishing media : water jet

Hazardous combustion products : nitrous gases
fumes/smoke
isocyanate vapor

Further information : Keep containers cool by spraying with water if exposed to fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special protective equipment for fire-fighters : Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Clear area.
Ensure adequate ventilation.
Avoid dust formation.
Wear suitable personal protective clothing and equipment.

Environmental precautions : Contain contaminated water/firefighting water.
Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up : Dike spillage.
If temporary control of isocyanate vapor is required, a blanket of protein foam or other suitable foam (available from most fire departments) may be placed over the spill. Transfer as much liquid as possible via pump or vacuum device into closed but not sealed containers for disposal.
Absorb isocyanate with suitable absorbent material (see § 40 CFR, sections 260, 264 and 265 for further information).
Do not make container pressure tight.
Move container to a well-ventilated area (outside).
Add at a 10 to 1 ratio.
Mixture of 90 % water, 5-8 % household ammonia, 2-5 %

SAFETY DATA SHEET

Sikaflex NP 1 white Formerly MSeal NP 1 White



Version 1.4	Revision Date: 02/02/2022	SDS Number: 000000641358	Date of last issue: 01/05/2021 Date of first issue: 04/27/2020
----------------	------------------------------	-----------------------------	---

detergent.
Allow to stand for at least 48 hours to allow escape of evolved carbon dioxide.
Wash down spill area with decontamination solution.

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Avoid dust formation.
Provide appropriate exhaust ventilation at places where dust is formed.

Advice on safe handling : Provide suitable exhaust ventilation at the processing machines.
Ensure thorough ventilation of stores and work areas.
Avoid aerosol formation.
When handling heated product, vapours of the product should be ventilated, and respiratory protection used.
Wear respiratory protection when spraying.
Avoid contact with skin and eyes.
Danger of bursting when sealed gastight.
Protect against moisture.
If bulging of drum occurs, transfer to well ventilated area, puncture to relieve pressure, open vent and let stand for 48 hours before resealing.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Keep only in the original container in a cool, well-ventilated place.
Protect from direct sunlight.
Store protected against freezing.

Recommended storage temperature : 41 - 90 °F / 5 - 32 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
toluene-2,6-diisocyanate	91-08-7	C	0.02 ppm 0.14 mg/m3	OSHA Z-1
		TWA (Inhalable fraction)	0.001 ppm	ACGIH

SAFETY DATA SHEET

Sikaflex NP 1 white Formerly MSeal NP 1 White



Version 1.4 Revision Date: 02/02/2022 SDS Number: 000000641358 Date of last issue: 01/05/2021
 Date of first issue: 04/27/2020

		and vapor)		
		STEL (Inhalable fraction and vapor)	0.005 ppm	ACGIH
		TWA	0.005 ppm 0.04 mg/m3	OSHA P0
		STEL	0.02 ppm 0.15 mg/m3	OSHA P0
calcium oxide	1305-78-8	TWA	2 mg/m3	ACGIH
		TWA	2 mg/m3	NIOSH REL
		TWA	5 mg/m3	OSHA Z-1
		TWA	5 mg/m3	OSHA P0
Limestone	1317-65-3	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium carbonate)	NIOSH REL
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
talc	14807-96-6	TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (respirable dust fraction)	2 mg/m3	OSHA P0
		TWA (Respirable)	2 mg/m3	NIOSH REL
		TWA	0.1 fibres per cubic centimeter	ACGIH
		TWA (Respirable particulate matter)	2 mg/m3	ACGIH
Stoddard solvent	8052-41-3	TWA	100 ppm	ACGIH
		TWA	350 mg/m3	NIOSH REL
		C	1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,900 mg/m3	OSHA Z-1
		TWA	100 ppm	OSHA P0

SAFETY DATA SHEET

Sikaflex NP 1 white Formerly MSeal NP 1 White



Version 1.4	Revision Date: 02/02/2022	SDS Number: 000000641358	Date of last issue: 01/05/2021 Date of first issue: 04/27/2020
----------------	------------------------------	-----------------------------	---

			525 mg/m3	
--	--	--	-----------	--

Personal protective equipment

- Respiratory protection : When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.
When atmospheric levels may exceed the occupational exposure limit (PEL or TLV) NIOSH-certified air-purifying respirators equipped with an organic vapor sorbent and particulate filter can be used as long as appropriate precautions and change out schedules are in place.
For emergency or non-routine, high exposure situations, including confined space entry, use a NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied-air respirator (SAR) with escape provisions.
- Hand protection
- Remarks : Chemical resistant protective gloves should be worn to prevent all skin contact. Suitable materials may include chloroprene rubber (Neoprene) nitrile rubber (Buna N) chlorinated polyethylene polyvinylchloride (Pylox) butyl rubber depending upon conditions of use.
- Eye protection : Tightly fitting safety goggles (chemical goggles).
Wear face shield if splashing hazard exists.
- Skin and body protection : Cover as much of the exposed skin as possible to prevent all skin contact.
Suitable materials may include saran-coated material depending upon conditions of use.
- Protective measures : Wear protective clothing as necessary to prevent contact.
Eye wash fountains and safety showers must be easily accessible.
Observe the appropriate PEL or TLV value.
- Hygiene measures : When using, do not eat, drink or smoke.
Hands and/or face should be washed before breaks and at the end of the shift.
Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : paste
- Color : white

SAFETY DATA SHEET

Sikaflex NP 1 white Formerly MSeal NP 1 White



Version 1.4	Revision Date: 02/02/2022	SDS Number: 000000641358	Date of last issue: 01/05/2021 Date of first issue: 04/27/2020
----------------	------------------------------	-----------------------------	---

Odor	:	mild
Odor Threshold	:	not determined
pH	:	No data available
Melting point	:	No data available
Freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	does not flash
Evaporation rate	:	No data available
Flammability (solid, gas)	:	not flammable Method: Manual of tests and criteria. Test N.1 (United Nations Recommendations on the Transport of Dangerous Goods).
Self-ignition	:	not self-igniting
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Relative density	:	No data available
Density	:	10.1 lb/USg (77 °F / 25 °C)
Solubility(ies)		
Water solubility	:	insoluble (59 °F / 15 °C)
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	No data available
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity		
Viscosity, dynamic	:	Not applicable

SAFETY DATA SHEET

Sikaflex NP 1 white Formerly MSeal NP 1 White



Version 1.4	Revision Date: 02/02/2022	SDS Number: 000000641358	Date of last issue: 01/05/2021 Date of first issue: 04/27/2020
----------------	------------------------------	-----------------------------	---

Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	Not an oxidizer.
Self-heating substances	:	No data available
Sublimation point	:	No data available
Molecular weight	:	No data available.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No hazardous reactions if stored and handled as prescribed/indicated.
Chemical stability	:	The product is stable if stored and handled as prescribed/indicated.
Possibility of hazardous reactions	:	Reacts with water, with formation of carbon dioxide. Risk of bursting. Reacts with alcohols. Reacts with acids. Reacts with alkalis. Reacts with amines. Risk of exothermic reaction. Risk of polymerization. Contact with certain rubbers and plastics can cause brittleness of the substance/product with subsequent loss in strength. No decomposition if stored and applied as directed.
Conditions to avoid	:	Avoid moisture.
Incompatible materials	:	Acids Amines Alcohols Water Alkalines Strong bases Substances/products that react with isocyanates.
Hazardous decomposition products	:	gases/vapours Carbon oxides nitrogen oxides hydrogen cyanide Aromatic isocyanates

SAFETY DATA SHEET

Sikaflex NP 1 white Formerly MSeal NP 1 White



Version 1.4 Revision Date: 02/02/2022 SDS Number: 000000641358 Date of last issue: 01/05/2021
 Date of first issue: 04/27/2020

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if inhaled.

Product:

Acute inhalation toxicity : ATE: 14.8 mg/l
 Remarks: Determined for vapor

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer.

IARC	Group 2B: Possibly carcinogenic to humans	
	Titanium dioxide	13463-67-7
	Group 2B: Possibly carcinogenic to humans	
	toluene-2,6-diisocyanate	91-08-7
	(toluene diisocyanates)	

NTP	Reasonably anticipated to be a human carcinogen	
	toluene-2,6-diisocyanate	91-08-7

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Health injuries are not known or expected under normal use.

SAFETY DATA SHEET

Sikaflex NP 1 white Formerly MSeal NP 1
White

Version 1.4	Revision Date: 02/02/2022	SDS Number: 000000641358	Date of last issue: 01/05/2021 Date of first issue: 04/27/2020
----------------	------------------------------	-----------------------------	---

The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity**Product:****Ecotoxicology Assessment**

Acute aquatic toxicity : This product has no known ecotoxicological effects.
Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regulations.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Do not discharge into drains/surface waters/groundwater.
Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

SAFETY DATA SHEET

Sikaflex NP 1 white Formerly MSeal NP 1 White



Version 1.4 Revision Date: 02/02/2022 SDS Number: 000000641358 Date of last issue: 01/05/2021
 Date of first issue: 04/27/2020

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
toluene-2,6-diisocyanate	91-08-7	100	21097

SARA 313

: The following components are subject to reporting levels established by SARA Title III, Section 313:

toluene-2,6-diisocyanate 91-08-7 >= 0.1 - < 1 %

US State Regulations

Pennsylvania Right To Know

Limestone 1317-65-3
 Titanium dioxide 13463-67-7
 talc 14807-96-6
 Stoddard solvent 8052-41-3
 calcium oxide 1305-78-8
 toluene-2,6-diisocyanate 91-08-7
 4-methyl-m-phenylene diisocyanate 584-84-9

New Jersey Right To Know

Limestone 1317-65-3
 Titanium dioxide 13463-67-7
 talc 14807-96-6
 Stoddard solvent 8052-41-3
 calcium oxide 1305-78-8
 toluene-2,6-diisocyanate 91-08-7

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer, and

SAFETY DATA SHEET

Sikaflex NP 1 white Formerly MSeal NP 1 White



Version 1.4 Revision Date: 02/02/2022 SDS Number: 000000641358 Date of last issue: 01/05/2021
 Date of first issue: 04/27/2020

toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

DSL : This product contains one or more components listed on the Canadian NDSL. All other components are on the Canadian DSL.

TSCA : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

TSCA list


The following substance(s) is/are subject to a Significant New Use Rule:
 toluene-2,6-diisocyanate 91-08-7
 4-methyl-m-phenylene diisocyanate 584-84-9

The following substance(s) is/are subject to TSCA 12(b) export notification requirements:
 toluene-2,6-diisocyanate 91-08-7

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	<input type="text"/>	<input type="text"/>
FLAMMABILITY	<input type="text"/>	
PHYSICAL HAZARD	<input type="text"/>	

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
 NIOSH REL : USA. NIOSH Recommended Exposure Limits
 OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
 OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants

SAFETY DATA SHEET

Sikaflex NP 1 white Formerly MSeal NP 1 White



Version	Revision Date:	SDS Number:	Date of last issue: 01/05/2021
1.4	02/02/2022	000000641358	Date of first issue: 04/27/2020

- OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIH / STEL : Short-term exposure limit
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- NIOSH REL / C : Ceiling value not be exceeded at any time.
- OSHA P0 / TWA : 8-hour time weighted average
- OSHA P0 / STEL : Short-term exposure limit
- OSHA Z-1 / TWA : 8-hour time weighted average
- OSHA Z-1 / C : Ceiling
- OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 02/02/2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

SAFETY DATA SHEET

**Sikaflex NP 1 white Formerly MSeal NP 1
White**



Version 1.4	Revision Date: 02/02/2022	SDS Number: 000000641358	Date of last issue: 01/05/2021 Date of first issue: 04/27/2020
----------------	------------------------------	-----------------------------	---

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

UNITIS
CONTRACTOR SUPPLIES