



SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION								
Product:	DECK-O-WELD.		Part Number: 3680000					
Manufacturer:	W. R. MEADOWS OF SOUTHERN CALIFORNIA		Address: 2300 Valley Boulevard Pomona, California 91768					
Telephone:	(909) 469-2606		In case of emergency, dial (800) 424-9300 (CHEMTREC)					
Revision Date:	9/27/2022							
Product Use:	Adhesive/Glue							
SECTION 2: HAZARDS IDENTIFICATION/EXPOSURE LIMITS								
	HMIS		HAZARD STATEMENTS					
Health	1		WARNING!					
Flammability	0		Causes skin irritation. (Category 2)					
Reactivity	0		Causes eye irritation. (Category 2B)					
Personal Protection			PRECAUTIONARY STATEMENTS					
			Avoid direct contact.					
			Avoid inhalation of mists/aerosols.					
SECTION 3: HAZARDS COMPONENTS								
	CAS	% by	SARA	Vapor Pressure	LEL			
Chemical Name:	Number	Weight	313	(mm Hg@20°C)	(@25°C)			
1. Vinyl Acetate Homopolymer	9003-20-7	50-55	No	N/A	N/A	N/A: Not Applicable		
Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1966 (SARA) and 40 CFR Part 372, chemicals listed on the 313 List (40 CFR Part 373.65) are identified under the heading "SARA 313."								
SECTION 4: EMERGENCY AND FIRST AID PROCEDURES								
EYE CONTACT: Immediately flush eyes with large quantities of water for fifteen (15) minutes. If irritation persists, seek medical attention.								
SKIN CONTACT: Wash skin with mild soap and water. Remove contaminated clothing. Launder before reuse. If irritation develops/persists, seek medical attention.								
INHALATION: Remove victim from exposure source and into fresh air. Treat symptomatically. If symptoms persist, seek medical attention.								
INGESTION: Give victim one to two glasses of water or milk to drink. Do not induce vomiting. Seek medical attention.								
MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND CHRONIC: See Section Eleven for Symptoms/Effects.								
SECTION 5: FIRE AND EXPLOSIVES HAZARDS								
FLASHPOINT: Not applicable, water-based product.								
EXTINGUISHING MEDIA: Water fog, foam, dry chemical or carbon dioxide.								
CHEMICAL/COMBUSTION HAZARDS: Carbon monoxide, carbon dioxide, and incomplete combustion products.								
PRECAUTIONS/PERSONAL PROTECTIVE EQUIPMENT: Self-contained breathing apparatus and full fire-fighting protective gear.								
SECTION 6: ACCIDENTAL RELEASE MEASURES								
SPILL OR LEAK PROCEDURES: Evacuate unauthorized personnel. Dike/contain spilled material. Remove spill source. Spilled materials should be cleaned up using an appropriate absorbent and placed in marked, sealed containers for disposal. Prevent spilled material from entering sewers, waterways, etc... Dried material may be difficult to remove.								
SECTION 7: HANDLING AND STORAGE								
SAFE HANDLING PROCEDURES: Avoid direct contact.								
SAFE STORAGE: Keep containers closed when not in use. Prevent product from freezing.								
SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION								
		OSHA			ACGIH			
Chemical Name:	PEL	PEL/CEILING	PEL/STEL	SKIN	TWA	TLV/CEILING	TLV/STEL	SKIN
1. Vinyl Acetate Homopolymer	N/E	N/E	N/E	No	N/E	N/E	N/E	No
ENGINEERING CONTROLS: None required under normal use conditions.								
PERSONAL PROTECTIVE EQUIPMENT: Safety glasses, chemical-resistant gloves. N/E: Not Established								

SAFETY DATA SHEET

Date of Preparation: 9/27/22		Page 2 of 2	3680000
SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES			
BOILING POINT: > 212 °F	VAPOR DENSITY: >1 (air=1)	% VOLATILE BY VOLUME: N/E	
EVAPORATION RATE: <1 (BuAc =1)	pH LEVEL: 5.0 (Approximate)	% VOLATILE BY WEIGHT: 44-46	
WEIGHT PER GALLON: 9.1	PRODUCT APPEARANCE: Milky Liquid	VOC CONTENT: 5 g/L	
ODOR: None	ODOR THRESHOLD: N/D	MELTING/FREEZING POINT: N/D	
FLASH POINT: See Section 5	FLAMMABILITY: See Section 5	UEL/LEL: N/D	
VAPOR PRESSURE: N/D	RELATIVE DENSITY: N/D	SOLUBILITY: N/D	
PARTITION COEFFICIENT: N/D	AUTOIGNITION TEMPERATURE: N/D	DECOMPOSITION TEMPERATURE: N/D	
VISCOSITY: N/D	N/D: Not Determined	N/E: Not Established	
SECTION 10: STABILITY/REACTIVITY			
STABILITY: Stable.		HAZARDOUS POLYMERIZATION: Will not occur.	
CONDITIONS AND MATERIALS TO AVOID: None recognized.			
HAZARDOUS DECOMPOSITION PRODUCTS: Acetic acid and Acrolein.			
SECTION 11: TOXICOLOGICAL INFORMATION			
EYE CONTACT: Direct contact may result in mild to moderate irritation.			
SKIN CONTACT: Direct contact may result in mild irritation.			
INHALATION: Inhalation of mists/aerosols may result in mild irritation.			
INGESTION: Not anticipated to be an exposure route.			
SIGNS AND SYMPTOMS: Symptoms of eye irritation include pain, tearing, redness, and swelling. Symptoms of skin irritation include reddening, swelling, rash, and redness. Symptoms of respiratory irritation include runny nose, sore throat, coughing, chest discomfort, shortness of breath, and reduced lung function.			
AGGRAVATED MEDICAL CONDITIONS: None recognized.			
OTHER HEALTH EFFECTS: None recognized.			
SECTION 12: ECOLOGICAL INFORMATION			
ECOTOXICITY: N/E	DEGRADABILITY: N/E	BIOACCUMULATIVE POTENTIAL: N/E	
SOIL MOBILITY: N/E	OTHER ADVERSE EFFECTS: N/E	N/E: Not Established	
SECTION 13: WASTE DISPOSAL INFORMATION			
WASTE DISPOSAL INFORMATION: Product is a non-hazardous waste. Solidified product may be landfilled.			
SECTION 14: TRANSPORTATION INFORMATION			
HAZARDOUS/NON-HAZARDOUS MATERIAL: Non-hazardous.			
UN NUMBER: None.	HAZARD CLASS: None.	PACKING GROUP: None.	
UN PROPER SHIPPING NAME: None.			
ENVIRONMENTAL HAZARDS: None.			
BULK TRANSPORTATION INFORMATION: Not regulated by DOT.			
SPECIAL PRECAUTIONS: None.			
SECTION 15: REGULATORY INFORMATION			
OTHER REGULATORY CONSIDERATIONS: None.			
SECTION 16: OTHER INFORMATION			
PREPARATION DATE:	9/27/2022		
PREPARED BY:	Dave Carey		

The information contained herein is based on the data available to us and is believed to be correct. However, we make no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injury from the use of this product described herein.