



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
US OSHA Hazard Communication Standard (29 CFR 1910.1200)

Revision Date 22-Nov-2023

Version 5

1. Identification

Product identifier

Product Name Stampable Overlay

Other means of identification

Product Code SC-60

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Restricted to professional users

Restrictions on use Consumer use

Details of the supplier of the safety data sheet

Supplier Address

Solomon Colors, Inc.
4050 Color Plant Road
Springfield, IL
62702

Manufacturer Address

Solomon Colors, Inc.
4050 Color Plant Road
Springfield, IL
62702

Emergency telephone number

Company Phone Number 800-624-0261 (US & Canada);

24 Hour Emergency Phone Number 800-373-7542

Emergency Telephone Hazmat Services 1-800-373-7542

2. Hazard(s) identification

Classification

Skin corrosion/irritation	Category 1
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1A
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1

Hazards not otherwise classified (HNOC)

Not applicable

Label elements



Danger

Hazard statements

Causes severe skin burns and eye damage
 May cause an allergic skin reaction
 May cause cancer
 May cause respiratory irritation
 Causes damage to organs through prolonged or repeated exposure

Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Use only outdoors or in a well-ventilated area
 Do not breathe dust/fume/gas/mist/vapors/spray
 Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 Immediately call a POISON CENTER or doctor/physician
 IF INHALED: Remove person to fresh air and keep comfortable for breathing

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other Information

No information available.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Chemical name	CAS No	Weight-%	Trade secret
Quartz, Crystalline Silica	14808-60-7	60-70	*
Portland Cement	65997-15-1	20-30	*
Limestone	1317-65-3	< 4	*
Silica (chemically prepared)	7631-86-9	< 5	*
Calcium hydroxide	1305-62-0	1-1.2	*
Formic acid, calcium salt	544-17-2	< 0.5	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Description of first aid measures

General advice	Get medical attention immediately if symptoms occur. Show this safety data sheet to the doctor in attendance.
Inhalation	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention immediately if symptoms occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. If symptoms persist, call a physician.
Skin contact	Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.
Self-protection of the first aider	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Symptoms	Burning sensation. Difficulty in breathing. Coughing and/ or wheezing. May cause allergic skin reaction. See Section 11 for additional Toxicological Information.
Effects of Exposure	See Section 11 for additional Toxicological Information. General: Prolonged or repeated inhalation may damage lungs. Inhalation: May cause respiratory irritation, sneezing, coughing, burning sensation in the throat or constriction of the larynx, or difficulty breathing. Eye contact: Redness, irritation or pain. Skin: Prolonged contact with large amounts of this product may cause mechanical irritation. Dust may cause irritation in skin folds or by contact in combination with tight clothing. Ingestion: Abdominal pain. Chronic symptoms: Shortness of breath, wheezing, cough and sputum production. May cause cancer, silicosis, lung disease, autoimmune disease, tuberculosis, and nephrotoxicity.

Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically.
---------------------------	------------------------

5. Fire-fighting measures

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.
Specific hazards arising from the chemical	No information available.
Hazardous combustion products	Thermal decomposition can lead to the release of irritating gases and vapors. Carbon oxides. Metal Oxides. Oxides of sulfur.
Explosion data	
Sensitivity to mechanical impact	None.

Sensitivity to static discharge None.

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Ensure adequate ventilation. Avoid contact with skin, eyes or clothing. Avoid breathing dust/fume/gas/mist/vapors/spray.

Other information Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Cover powder spill with plastic sheet or tarp to minimize spreading. Do not touch or walk through spilled material. Prevent dust cloud.

Methods for cleaning up Avoid generation of dust. Do not dry sweep dust. Wet dust with water before sweeping or use a vacuum to collect dust. Pick up and transfer to properly labeled containers. Use personal protective equipment as required.

7. Handling and storage

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children.

8. Exposure controls/personal protection

Control parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Quartz, Crystalline Silica 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	TWA: 50 µg/m ³ TWA: 50 µg/m ³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m ³ respirable dust : (250)/(%SiO ₂ + 5) mppcf	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust

		TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	
Portland Cement 65997-15-1	TWA: 1 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction TWA: 50 mppcf <1% Crystalline silica	IDLH: 5000 mg/m ³ TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Limestone 1317-65-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Silica (chemically prepared) 7631-86-9	-	TWA: 50 µg/m ³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 6 mg/m ³ <1% Crystalline silica TWA: 20 mppcf : (80)/(% SiO ₂) mg/m ³ TWA	IDLH: 3000 mg/m ³ TWA: 6 mg/m ³
Calcium hydroxide 1305-62-0	TWA: 5 mg/m ³	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ not in effect as a result of reconsideration	TWA: 5 mg/m ³

Appropriate engineering controls

Engineering controls

Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tight sealing safety goggles.

Hand protection

Protective gloves.

Skin and body protection

Wear suitable protective clothing.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

General hygiene considerations

Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state	Powder
Appearance	Gray / White Powder
Color	White; /; Gray
Odor	Odorless
Odor threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	None known
pH (as aqueous solution)		None known
Melting point/freezing point	> 1000 °C / 1832 °F	None known
Boiling point / boiling range	No data available	None known
Flash point	No data available	None known
Evaporation rate	Not Applicable	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability limit:	No data available	
Lower flammability limit:	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	No data available	None known
Water solubility	No data available	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

Other information

Explosive properties	No information available
Oxidizing properties	No information available
Softening point	No information available
Molecular weight	No information available
VOC Content (%)	Not applicable
Density	No information available
Bulk density	No information available

10. Stability and reactivity

Reactivity	Contact with acids liberates toxic gas.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None under normal processing.
Conditions to avoid	Do not freeze.
Incompatible materials	Strong acids. Strong bases. Strong oxidizing agents.
Hazardous decomposition products	Thermal decomposition can lead to release of irritating and toxic gases and vapors. Carbon oxides. Sulfur oxides. Metal Oxides.

11. Toxicological information

Information on likely routes of exposure

Product Information	No data available. Data is for major component in product.
----------------------------	--

Inhalation	Harmful by inhalation. May cause irritation of respiratory tract.
Eye contact	Causes serious eye damage. May cause irreversible damage to eyes.
Skin contact	May cause irritation. Contact causes severe skin irritation and possible burns. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.
Ingestion	May be harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Can burn mouth, throat, and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. Burning. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. May cause allergic skin reaction.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	5,203.70 mg/kg
ATEmix (dermal)	4,399.80 mg/kg
ATEmix (inhalation-gas)	> 20,000 ppm
ATEmix (inhalation-dust/mist)	> 5 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Silica (chemically prepared) 7631-86-9	= 7900 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	> 58.8 mg/L (Rat) 4 h
Calcium hydroxide 1305-62-0	= 7340 mg/kg (Rat)	> 2500 mg/kg (Rat)	> 6.04 mg/L (Rat) 4 h
Formic acid, calcium salt 544-17-2	= 2650 mg/kg (Rat)	-	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	May cause skin irritation. Classification based on data available for ingredients.
Serious eye damage/eye irritation	Classification based on data available for ingredients. Causes burns. Causes serious eye damage.
Respiratory or skin sensitization	Repeated or prolonged contact may cause allergic reactions in very susceptible persons. Classification based on individual ingredients of the mixture.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.

Carcinogenicity Contains a known or suspected carcinogen. May cause cancer. Classification based on data available for ingredients.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Quartz, Crystalline Silica 14808-60-7	A2	Group 1	Known	X
Silica (chemically prepared) 7631-86-9	-	Group 3	Known	X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity	Contains a known or suspected reproductive toxin. Classification based on data available for ingredients.
STOT - single exposure	May cause respiratory irritation. May cause drowsiness or dizziness.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Target organ effects	Respiratory system, Eyes, Skin, Lungs.
Aspiration hazard	Not applicable.
Other adverse effects	Causes damage to lungs through prolonged or repeated exposure if inhaled. Overexposure to dust can cause chronic lung injury such as chronic silicosis, accelerated silicosis, and acute silicosis. Several studies have also reported excess cases of kidney diseases in silica exposed workers.
Interactive effects	No information available.

12. Ecological information

Ecotoxicity The environmental impact of this product has not been fully investigated.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Silica (chemically prepared) 7631-86-9	EC50: =440mg/L (72h, Pseudokirchneriella subcapitata)	LC50: =5000mg/L (96h, Brachydanio rerio)	-	EC50: =7600mg/L (48h, Ceriodaphnia dubia)
Formic acid, calcium salt 544-17-2	-	LC50: >=1000mg/L (96h, Brachydanio rerio)	-	-

Persistence and degradability No information available.

Bioaccumulation There is no data for this product.

Mobility Slightly soluble in water.

Other adverse effects No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

California Hazardous Waste Status This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. Transport information

DOT Not regulated

15. Regulatory information

International Inventories

TSCA Complies.

Chemical name	CAS No	US TSCA Inventory listing	US TSCA inactive/active designation
Limestone	1317-65-3	Present	Active

DSL/NDSL Complies.
EINECS/ELINCS Complies.
ENCS Does not comply.
IECSC Complies.
KECL Complies.
PICCS Does not comply.
AIIC Contact supplier for inventory compliance status.
NZIoC Complies.

Legend:

- TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
- ENCS** - Japan Existing and New Chemical Substances
- IECSC** - China Inventory of Existing Chemical Substances
- KECL** - Korean Existing and Evaluated Chemical Substances
- PICCS** - Philippines Inventory of Chemicals and Chemical Substances
- AIIC** - Australian Inventory of Industrial Chemicals
- NZIoC** - New Zealand Inventory of Chemicals

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
Quartz, Crystalline Silica - 14808-60-7	Carcinogen
Silica (chemically prepared) - 7631-86-9	Carcinogen
Formaldehyde - 50-00-0	Carcinogen
Lead - 7439-92-1	Carcinogen Developmental Female Reproductive Male Reproductive
Acetaldehyde - 75-07-0	Carcinogen
Hexavalent chromium - 18540-29-9	Carcinogen Developmental Female Reproductive Male Reproductive
Nickel Compounds - RR-00800-4	Carcinogen
Ethylbenzene - 100-41-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Quartz, Crystalline Silica 14808-60-7	X	X	X
Portland Cement 65997-15-1	X	X	X
Limestone 1317-65-3	X	X	X
Silica (chemically prepared) 7631-86-9	-	X	X
Calcium hydroxide 1305-62-0	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA	Health hazards 3	Flammability 0	Instability 0	Special hazards -
HMIS	Health hazards 3*	Flammability 0	Physical hazards 0	Personal protection X
<i>Chronic Hazard Star Legend</i>	<i>* = Chronic Health Hazard</i>			

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation

Key literature references and sources for data used to compile the SDS

- Agency for Toxic Substances and Disease Registry (ATSDR)
- U.S. Environmental Protection Agency ChemView Database
- European Food Safety Authority (EFSA)
- EPA (Environmental Protection Agency)
- Acute Exposure Guideline Level(s) (AEGl(s))
- U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
- U.S. Environmental Protection Agency High Production Volume Chemicals
- Food Research Journal
- Hazardous Substance Database
- International Uniform Chemical Information Database (IUCLID)
- National Institute of Technology and Evaluation (NITE)
- Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
- NIOSH (National Institute for Occupational Safety and Health)
- National Library of Medicine's ChemID Plus (NLM CIP)
- National Library of Medicine's PubMed database (NLM PUBMED)
- National Toxicology Program (NTP)
- New Zealand's Chemical Classification and Information Database (CCID)
- Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
- Organization for Economic Co-operation and Development High Production Volume Chemicals Program
- Organization for Economic Co-operation and Development Screening Information Data Set
- World Health Organization

Prepared By	Solomon Colors.
Revision Date	22-Nov-2023
Revision Note	Periodic Review.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.