

**SAFETY DATA SHEET**

according to the OSHA Hazard Communication Standard

**Sikalastic M 200 SLV Formerly MSeal M 200SLV**

Version 2.0      Revision Date: 08/08/2025      SDS Number: 000000265071      Date of last issue: 01/08/2021  
 Date of first issue: 05/22/2020

**SECTION 1. IDENTIFICATION**

Product name : Sikalastic M 200 SLV Formerly MSeal M 200SLV  
 Product code : 000000000055393521

**Manufacturer or supplier's details**

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE  
 Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

National Emergency Telephone Number : USA: +1-800-255-3924 ChemTel contract no. MIS9240420

**Recommended use of the chemical and restrictions on use**

Recommended use : Coating

Restrictions on use : Reserved for industrial and professional use.

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Flammable liquids : Category 3

Acute toxicity (Inhalation - vapour) : Category 3

Respiratory sensitization : Category 1

Skin sensitization : Category 1

Carcinogenicity : Category 2

Reproductive toxicity : Category 1B

Specific target organ toxicity - repeated exposure : Category 1 (Central nervous system)

**Other hazards**

Contains isocyanates. Inhalation of isocyanate mists or vapors may cause respiratory irritation, breathlessness, chest discomfort and reduced pulmonary function. Overexposure well above the PEL may result in bronchitis, bronchial spasms and pulmonary edema. Animal tests indicate that skin contact may play a role in causing respiratory sensitization.

**SAFETY DATA SHEET**

according to the OSHA Hazard Communication Standard



**Sikalastic M 200 SLV Formerly MSeal M 200SLV**

Version 2.0      Revision Date: 08/08/2025      SDS Number: 000000265071      Date of last issue: 01/08/2021  
 Date of first issue: 05/22/2020

**GHS label elements**

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.  
 H331 Toxic if inhaled.  
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
 H317 May cause an allergic skin reaction.  
 H351 Suspected of causing cancer.  
 H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.  
 H360 May damage fertility or the unborn child.

Precautionary Statements :

**Prevention:**

- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
- P260 Do not breathe dusts or mists.
- P201 Obtain special instructions before use.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P202 Do not handle until all safety precautions have been read and understood.
- P243 Take action to prevent static discharges.
- P284 In case of inadequate ventilation wear respiratory protection.
- P264 Wash face, hands and any exposed skin thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P242 Use only non-sparking tools.
- P240 Ground and bond container and receiving equipment.
- P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

**Response:**

- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
- P362 + P364 Take off contaminated clothing and wash it before reuse.
- P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.
- P311 Call a POISON CENTER or doctor/ physician.

**SAFETY DATA SHEET**

according to the OSHA Hazard Communication Standard



**Sikalastic M 200 SLV Formerly MSeal M 200SLV**

Version 2.0      Revision Date: 08/08/2025      SDS Number: 000000265071      Date of last issue: 01/08/2021  
 Date of first issue: 05/22/2020

**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.  
 P233 Keep container tightly closed.  
 P405 Store locked up.

**Disposal:**

P501 Dispose of contents/container to appropriate hazardous waste collection point.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : polyurethane

**Components**

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Stoddard solvent	8052-41-3*	>= 0 - < 20	-
toluene-2,6-diisocyanate	91-08-7*	>= 0.3 - < 3	-
trimethoxy(3-(oxiranyl-methoxy)propyl)silane	2530-83-8*	>= 0 - < 1	-
4-methyl-m-phenylene diisocyanate	584-84-9*	>= 0.1 - < 0.3	-
dibutyltin dilaurate	77-58-7*	>= 0 - < 0.3	-
Limestone	1317-65-3*	>= 10 - < 50	-
Titanium dioxide	13463-67-7*	>= 0 - < 5	-
Calcium sulphate	7778-18-9*	>= 0 - < 5	-
talc	14807-96-6*	>= 0 - < 15	-

\* Indicates that the identifier is a CAS No.

**SECTION 4. FIRST AID MEASURES**

General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

If inhaled : Keep patient calm, remove to fresh air. If symptoms persist, seek medical advice.

In case of skin contact : After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

**SAFETY DATA SHEET**

according to the OSHA Hazard Communication Standard



**Sikalastic M 200 SLV Formerly MSeal M 200SLV**

Version	Revision Date:	SDS Number:	Date of last issue: 01/08/2021
2.0	08/08/2025	000000265071	Date of first issue: 05/22/2020

- In case of eye contact : Contact lenses should be removed. Hold eyelids open and flush with copious amounts of clean, fresh water or a special eyewash solution and seek medical advice.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction. Toxic if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected of causing cancer. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.
- Notes to physician : Treat symptomatically.

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO2)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Hazardous combustion products : fumes/smoke  
harmful vapours  
Carbon oxides  
nitrogen oxides  
carbon black
- Further information : The degree of risk is governed by the burning substance and the fire conditions.  
If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Contaminated extinguishing water must be disposed of in accordance with official regulations.
- Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.

**SAFETY DATA SHEET**

according to the OSHA Hazard Communication Standard



**Sikalastic M 200 SLV Formerly MSeal M 200SLV**

Version	Revision Date:	SDS Number:	Date of last issue: 01/08/2021
2.0	08/08/2025	000000265071	Date of first issue: 05/22/2020

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Contain contaminated water/firefighting water.  
Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).  
Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapors/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Prevent unauthorized access.  
No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with

**SAFETY DATA SHEET**

according to the OSHA Hazard Communication Standard



**Sikalastic M 200 SLV Formerly MSeal M 200SLV**

Version 2.0      Revision Date: 08/08/2025      SDS Number: 000000265071      Date of last issue: 01/08/2021  
 Date of first issue: 05/22/2020

the technological safety standards.

Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
dibutyltin dilaurate	77-58-7	TWA	0.1 mg/m3 (Tin)	OSHA Z-1
		TWA	0.1 mg/m3 (Tin)	ACGIH
		STEL	0.2 mg/m3 (Tin)	ACGIH
		TWA	0.1 mg/m3 (Tin)	OSHA P0
		TWA	0.1 mg/m3 (Tin)	NIOSH REL
toluene-2,6-diisocyanate	91-08-7	C	0.02 ppm 0.14 mg/m3	OSHA Z-1
		TWA (Inhalable fraction and vapor)	0.001 ppm	ACGIH
		STEL (Inhalable fraction and vapor)	0.005 ppm	ACGIH
		TWA	0.005 ppm 0.04 mg/m3	OSHA P0
		STEL	0.02 ppm 0.15 mg/m3	OSHA P0
		C	0.02 ppm 0.14 mg/m3	OSHA Z-1
4-methyl-m-phenylene diisocyanate	584-84-9	TWA (Inhalable fraction and vapor)	0.001 ppm	ACGIH
		STEL (Inhalable fraction and vapor)	0.005 ppm	ACGIH
		TWA	0.005 ppm 0.04 mg/m3	OSHA P0
		STEL	0.02 ppm 0.15 mg/m3	OSHA P0
Limestone	1317-65-3	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1

**SAFETY DATA SHEET**

according to the OSHA Hazard Communication Standard



**Sikalastic M 200 SLV Formerly MSeal M 200SLV**

Version 2.0      Revision Date: 08/08/2025      SDS Number: 000000265071      Date of last issue: 01/08/2021  
 Date of first issue: 05/22/2020

		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium carbonate)	NIOSH REL
Calcium sulphate	7778-18-9	TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Inhalable particulate matter)	10 mg/m3 (Calcium)	ACGIH
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (Respirable particulate matter)	0.2 mg/m3 (Titanium dioxide)	ACGIH
		TWA (Respirable particulate matter)	2.5 mg/m3 (Titanium dioxide)	ACGIH
talc	14807-96-6	TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (respirable dust fraction)	2 mg/m3	OSHA P0
		TWA (Respirable)	2 mg/m3	NIOSH REL
		TWA	0.1 fibres per cubic centimeter	ACGIH
		TWA (Respirable particulate matter)	2 mg/m3	ACGIH

**SAFETY DATA SHEET**

according to the OSHA Hazard Communication Standard



**Sikalastic M 200 SLV Formerly MSeal M 200SLV**

Version 2.0      Revision Date: 08/08/2025      SDS Number: 000000265071      Date of last issue: 01/08/2021  
 Date of first issue: 05/22/2020

Stoddard solvent	8052-41-3	TWA	100 ppm	ACGIH
		TWA	350 mg/m3	NIOSH REL
		C	1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,900 mg/m3	OSHA Z-1
		TWA	100 ppm 525 mg/m3	OSHA P0

**Engineering measures** : Ensure adequate ventilation.

**Personal protective equipment**

**Respiratory protection** : When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.  
 When atmospheric levels may exceed the occupational exposure limit (PEL or TLV) NIOSH-certified air-purifying respirators equipped with an organic vapor sorbent and particulate filter can be used as long as appropriate precautions and change out schedules are in place.

**Hand protection**

**Remarks** : Chemical resistant protective gloves should be worn to prevent all skin contact. Suitable materials may include chloroprene rubber (Neoprene) nitrile rubber (Buna N) chlorinated polyethylene polyvinylchloride (Pylox) butyl rubber fluoroelastomer (Viton) depending upon conditions of use. Manufacturer's directions for use should be observed because of great diversity of types.

**Eye protection**

: Tightly fitting safety goggles (chemical goggles).  
 Wear face shield if splashing hazard exists.

**Skin and body protection**

: Cover as much of the exposed skin as possible to prevent all skin contact.  
 Suitable materials may include saran-coated material depending upon conditions of use.

**Protective measures**

: Do not inhale dust/fumes/aerosols.  
 Avoid contact with the skin, eyes and clothing.  
 Avoid exposure.  
 Handle in accordance with good building materials hygiene and safety practice.  
 Wearing of closed work clothing is recommended.

**Hygiene measures**

: When using, do not eat, drink or smoke.  
 Hands and/or face should be washed before breaks and at the end of the shift.  
 At the end of the shift the skin should be cleaned and skin-care agents applied.  
 Gloves must be inspected regularly and prior to each use.

**SAFETY DATA SHEET**

according to the OSHA Hazard Communication Standard

**Sikalastic M 200 SLV Formerly MSeal M 200SLV**

Version	Revision Date:	SDS Number:	Date of last issue:
2.0	08/08/2025	000000265071	01/08/2021
			Date of first issue: 05/22/2020

Replace if necessary (e.g. pinhole leaks).

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	:	liquid
Color	:	gray
Odor	:	solvent
Odor Threshold	:	not determined
pH	:	neutral to slightly alkaline
Melting point/freezing point	:	No data available
Boiling point	:	approx. 347 °F / 175 °C
Flash point	:	109.9 °F / 43.3 °C
Evaporation rate	:	No data available
Flammability (liquids)	:	Flammable liquid and vapor.
Upper explosion limit / Upper flammability limit	:	7.0 %(V)
Lower explosion limit / Lower flammability limit	:	1.0 %(V)
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Relative density	:	No data available
Density	:	approx. 1.16 g/cm <sup>3</sup> (68 °F / 20 °C)
Solubility(ies)		
Water solubility	:	slightly soluble (68 °F / 20 °C)
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	not applicable for mixtures

**SAFETY DATA SHEET**

according to the OSHA Hazard Communication Standard

**Sikalastic M 200 SLV Formerly MSeal M 200SLV**

Version	Revision Date:	SDS Number:	Date of last issue: 01/08/2021
2.0	08/08/2025	000000265071	Date of first issue: 05/22/2020

Autoignition temperature	:	No data available
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity		
Viscosity, dynamic	:	approx. 4,000 - 9,000 mPa.s
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive Not explosive
Oxidizing properties	:	not fire-propagating
Sublimation point	:	No applicable information available.
Molecular weight	:	Not applicable
Metal corrosion rate	:	Corrosive effects to metal are not anticipated.

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	No hazardous reactions if stored and handled as prescribed/indicated.
Chemical stability	:	The product is stable if stored and handled as prescribed/indicated.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapors may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Strong acids Strong bases Strong oxidizing agents Strong reducing agents
Hazardous decomposition products	:	No hazardous decomposition products if stored and handled as prescribed/indicated.

**SECTION 11. TOXICOLOGICAL INFORMATION**

**Acute toxicity**  
Toxic if inhaled.

**Product:**

**SAFETY DATA SHEET**

according to the OSHA Hazard Communication Standard



**Sikalastic M 200 SLV Formerly MSeal M 200SLV**

Version	Revision Date:	SDS Number:	Date of last issue:
2.0	08/08/2025	000000265071	01/08/2021
			Date of first issue: 05/22/2020

Acute inhalation toxicity : ATE: 5.73 mg/l  
Remarks: Determined for vapor

**Skin corrosion/irritation**

Not classified based on available information.

**Serious eye damage/eye irritation**

Not classified based on available information.

**Respiratory or skin sensitization**

**Skin sensitization**

May cause an allergic skin reaction.

**Respiratory sensitization**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Suspected of causing cancer.

**Reproductive toxicity**

May damage fertility or the unborn child.

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

**Aspiration toxicity**

Not classified based on available information.

**Further information**

**Product:**

Remarks : Solvents may degrease the skin.

Remarks : The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**SAFETY DATA SHEET**

according to the OSHA Hazard Communication Standard



**Sikalastic M 200 SLV Formerly MSeal M 200SLV**

Version 2.0      Revision Date: 08/08/2025      SDS Number: 000000265071      Date of last issue: 01/08/2021  
 Date of first issue: 05/22/2020

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

**Product:**

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

Waste from residues : Dispose of in accordance with national, state and local regulations. Do not contaminate ponds, waterways or ditches with chemical or used container. Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product. Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION**

**International Regulations**

**UNRTDG**

UN number : UN 1263  
 Proper shipping name : PAINT  
 Class : 3  
 Packing group : III  
 Labels : 3  
 Environmentally hazardous : no

**IATA-DGR**

UN/ID No. : UN 1263  
 Proper shipping name : Paint  
 Class : 3  
 Packing group : III  
 Labels : Flammable Liquids  
 Packing instruction (cargo aircraft) : 366  
 Packing instruction (passenger aircraft) : 355

**SAFETY DATA SHEET**

according to the OSHA Hazard Communication Standard



**Sikalastic M 200 SLV Formerly MSeal M 200SLV**

Version 2.0      Revision Date: 08/08/2025      SDS Number: 000000265071      Date of last issue: 01/08/2021  
 Date of first issue: 05/22/2020

**IMDG-Code**

UN number : UN 1263  
 Proper shipping name : PAINT

Class : 3  
 Packing group : III  
 Labels : 3  
 EmS Code : F-E, S-E  
 Marine pollutant : no

**Transport in bulk according to IMO instruments**

Not applicable for product as supplied.

**Domestic regulation**

**49 CFR**

UN/ID/NA number : UN 1263  
 Proper shipping name : Paint

Class : 3  
 Packing group : III  
 Labels : FLAMMABLE LIQUID  
 ERG Code : 128  
 Marine pollutant : no

**Special precautions for user**

Remarks : Not dangerous goods of class 3 in packages up to 450 litres capacity (valid for ADR, ADNR, RID, TDG and USDOT).

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**SECTION 15. REGULATORY INFORMATION**

**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
toluene-2,6-diisocyanate	91-08-7	100	14224

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

toluene-2,6-diisocyanate      91-08-7  
 4-methyl-m-phenylene diisocyanate      584-84-9

**SAFETY DATA SHEET**

according to the OSHA Hazard Communication Standard



**Sikalastic M 200 SLV Formerly MSeal M 200SLV**

Version 2.0      Revision Date: 08/08/2025      SDS Number: 000000265071      Date of last issue: 01/08/2021  
 Date of first issue: 05/22/2020

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

**US State Regulations**

**Pennsylvania Right To Know**

toluene-2,6-diisocyanate	91-08-7
Limestone	1317-65-3
Calcium sulphate	7778-18-9
Titanium dioxide	13463-67-7
talc	14807-96-6
Stoddard solvent	8052-41-3
4-methyl-m-phenylene diisocyanate	584-84-9

**New Jersey Right To Know**

toluene-2,6-diisocyanate	91-08-7
Limestone	1317-65-3
Calcium sulphate	7778-18-9
Titanium dioxide	13463-67-7
talc	14807-96-6
Stoddard solvent	8052-41-3
4-methyl-m-phenylene diisocyanate	584-84-9

**California Prop. 65**

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer, and toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**The ingredients of this product are reported in the following inventories:**

DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

**TSCA list**

The following substance(s) is/are subject to a Significant New Use Rule:

toluene-2,6-diisocyanate	91-08-7	See 40 CFR § 721.10789; Proposed Rule
		Proposed Rule
4-methyl-m-phenylene diisocyanate	584-84-9	See 40 CFR § 721.10789; Proposed Rule
		Proposed Rule

The following substance(s) is/are subject to TSCA 12(b) export notification requirements:

toluene-2,6-diisocyanate	91-08-7
4-methyl-m-phenylene diisocyanate	584-84-9

**SAFETY DATA SHEET**

according to the OSHA Hazard Communication Standard




**Sikalastic M 200 SLV Formerly MSeal M 200SLV**

Version 2.0      Revision Date: 08/08/2025      SDS Number: 000000265071      Date of last issue: 01/08/2021  
 Date of first issue: 05/22/2020


**SECTION 16. OTHER INFORMATION**

**Further information**

**NFPA 704:**



**HMIS® IV:**



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

**Full text of other abbreviations**

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIH / STEL : Short-term exposure limit
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- NIOSH REL / C : Ceiling value not be exceeded at any time.
- OSHA P0 / TWA : 8-hour time weighted average
- OSHA P0 / STEL : Short-term exposure limit
- OSHA Z-1 / TWA : 8-hour time weighted average
- OSHA Z-1 / C : Ceiling
- OSHA Z-3 / TWA : 8-hour time weighted average

AiIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration asso-

**SAFETY DATA SHEET**

according to the OSHA Hazard Communication Standard



**Sikalastic M 200 SLV Formerly MSeal M 200SLV**

Version 2.0	Revision Date: 08/08/2025	SDS Number: 000000265071	Date of last issue: 01/08/2021 Date of first issue: 05/22/2020
----------------	------------------------------	-----------------------------	---

ciated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 08/08/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN