




GR8 Guard™ Grate Inlet Protection

GR8 Guard is a patent pending, low-cost drainage inlet protection system designed to keep sediment and debris out of grated storm drain inlets in paved areas. Water rises at least 1.5 inches before reaching the filter causing heavier particles to settle. The system filters storm water above the ground easing visual inspection and


maintenance. The system has a high flow bypass designed to reduce the chance of back ups. It is easy to fasten to the grate with wire ties, has a long life, is resistant to traffic, and reusable. During installation or cleaning, the grate does not need to be removed, reducing installer injuries.



100% American
Content / Labor



✓ Reusable
✓ Recyclable



Product Characteristics

Module weight (average lbs per sq. ft.)
Functional life (min years)
Reusable
Easy to clean
Seals extend past drain & filter core for good contact with hard surface

0.5
4
YES
YES
YES

Filter – min AOS (microns) 425
Tensile Yield ASTM D-638 (lb/in²) 1800 - 2800
Ultimate Tensile Strength: ASTM D-638 (lb/in²) 2000 - 2800
Filter Flow Rate ASTM D-4491 gpm/ft² (min) 145



Product Designation	Fits Grate Size:
GG 12x12	Grates up to 12"x12"
GG 20x20	All grates up to 20"x20"
GG 28x28	All grates up to 28"x28"
GG 36x24	All grates up to 36"x24"
GG 36x28	All grates up to 36"x28"
GG 36x36	All grates up to 36"x36"
GG 42x28	All grates up to 42"x28"
GG 48x24	All grates up to 48"x36"
GG 48x36	All grates up to 48"x36"
GG 48x48	All grates up to 48"x48"

Product Benefits

- Fast installation, no grate removal
- Above street, easy to inspect & clean
- Stands up to traffic
- Lower costs
- Long life, UV stable
- Reduces back injuries
- Durable – semi-permanent
- One installation per project

H29982 Updated: 01/21

©2006-21 ERTEC Environmental Systems
www.ertecsystems.com (866) 521-0724