



MasterFormat: 07 13 26

JULY 2023  
(Supersedes August 2012)

## POINTING MASTIC

### Cold-Applied, Single-Component Polymeric Sealing Compound

#### DESCRIPTION

POINTING MASTIC is a pre-mixed, cold-applied, polymeric, single-component sealing compound. POINTING MASTIC was specifically designed to seal all exterior, vertical, and horizontal terminations of MEL-ROL®, PRECON®, MEL-DEK™, AIR-SHIELD™, PERMINATOR®, and PREMOULDED MEMBRANE® VAPOR SEAL WITH PLASMATIC® CORE from W. R. MEADOWS. It is also used for adhesive bonding of PROTECTION COURSE and MEL-DRAIN™. The product can also be used with in applications of NEOPRENE FLASHING MEMBRANE with HRM 714. POINTING MASTIC can be used on all patches and overlaps in detail areas. It offers excellent cohesive and adhesive qualities when applied to structural concrete, masonry, and/or wood. Once applied, it provides excellent adhesive and bonding strengths. POINTING MASTIC cures to form a tough, flexible membrane.

#### USES

POINTING MASTIC is designed to meet a variety of building/construction product applications. These uses include sealing terminations for vertical or horizontal vaporproofing or waterproofing membranes, deck waterproofing systems, air barriers, and flashing membranes. The product can be used on metal flashings.

It is used for adhesive bonding of protection course boards and rolled matrix draining systems. POINTING MASTIC is also applied between membrane and clamping rings at all terminations, drains, and protrusions. In addition, POINTING MASTIC is ideal for sealing joints and concrete curbs and gutters. The product can also be used with sewer joints. POINTING MASTIC can be applied to seal top edge horizontal terminations as well as the inside and outside corners of overlapping detail strips.

#### FEATURES/BENEFITS

- Premixed and easy to apply with caulking gun or trowel.
- Excellent cohesive and adhesive strengths.
- Will not lose bond once applied.
- Specifically developed for use with detail strips, vaporproofing and waterproofing membranes, protection course boards, and rolled matrix drainage systems.

#### PACKAGING

29 Oz. (857.65 mL) Cartridges  
5 Gallon (18.93 Liter) Pails

#### COVERAGE

Approx. 200 lineal ft. (61 m) per gallon (3.79 L), when used as directed.

#### SHELF LIFE

When stored indoors and in original, unopened containers at temperatures between 40 - 90° F (4 - 32° C), shelf life is a minimum of two years from date of manufacture.

#### SPECIFICATIONS/STANDARDS

- Complies with U.S. EPA, LADCO, OTC, and SCAQMD maximum allowable VOC requirements.

#### APPLICATION

**Surface Preparation** ... All surfaces to receive an application of POINTING MASTIC should be dry, frost-free, clean, and free of all contaminants.

CONTINUED ON REVERSE SIDE ...

#### W. R. MEADOWS, INC.

P.O. Box 338 • Hampshire, IL 60140-0338  
Phone: 847/214-2100 • Fax: 847/683-4544  
1-800-342-5976  
www.wrmeadows.com • info@wrmeadows.com

HAMPSHIRE, IL / CARTERSVILLE, GA / YORK, PA  
FORT WORTH, TX / BENICIA, CA / POMONA, CA  
GOODYEAR, AZ / MILTON, ON / SHERWOOD PARK, AB

**Application Method** ... For easy application, store at temperatures of 60° F (16° C) or higher before using. Material will be stiffer and more difficult to work with at cooler temperatures. POINTING MASTIC can be easily applied with a caulking gun or trowel. Apply only in areas that will **not** be covered with a waterproofing membrane. Apply and spread the material to a thickness of approximately 1/8" (3.18 mm) in a strip 1 - 3" (25.4 - 76.2 mm) wide.

A bead of POINTING MASTIC is applied to the top edge horizontal termination of the vaporproofing or waterproofing membranes on vertical walls.

The corner and footing on inside corners are finished with POINTING MASTIC in the center of the detail strip where the vertical wall and footing meet. The outside corner is finished with POINTING MASTIC in the lower center point where vertical wall and footing meet.

POINTING MASTIC should also be applied at the laps around corners, extending 12" (305 mm) in each direction from the corner.

A bead of POINTING MASTIC should also be applied between membrane and clamping rings and at all terminations, drains, and protrusions.

Application temperature should coincide with the product it is being used with.

**Cleanup** ... Tools can be cleaned with mineral spirits at the end of each workday. Follow manufacturer's precautions when using a solvent as a cleaner.

### PRECAUTIONS

Apply only in areas that will **not** be covered with a waterproofing membrane. POINTING MASTIC VAPOR IS FLAMMABLE. Do not apply to foam - POINTING MASTIC contains solvent that may chemically react with the insulated concrete forms or foam insulation. Read and follow application information and Health and Safety information on product label.

For most recent data sheet, further LEED information, and SDS, visit [www.wrmeadows.com](http://www.wrmeadows.com).



#### LIMITED WARRANTY

W. R. MEADOWS, INC. warrants at the time and place we make shipment, our material will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. Read complete warranty. Copy furnished upon request.

#### Disclaimer

The information contained herein is included for illustrative purposes only, and to the best of our knowledge, is accurate and reliable. W. R. MEADOWS, INC. cannot however under any circumstances make any guarantee of results or assume any obligation or liability in connection with the use of this information. As W. R. MEADOWS, INC. has no control over the use to which others may put its product, it is recommended that the products be tested to determine if suitable for specific application and/or our information is valid in a particular circumstance. Responsibility remains with the architect or engineer, contractor and owner for the design, application and proper installation of each product. Specifier and user shall determine the suitability of products for specific application and assume all responsibilities in connection therewith.