

Safety Data Sheet
according to OSHA 1910.1200 Hazard Communication Standard



Sikacrete®-421 CI Rapid

Revision Date 07/18/2025

Print Date 07/18/2025

SECTION 1. IDENTIFICATION

Product name : Sikacrete®-421 CI Rapid

Company name : Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
USA
www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300
INTERNATIONAL: +1-703-527-3887

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion : Sub-category 1C

Serious eye damage : Category 1

Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 1A

Specific target organ toxicity - repeated exposure : Category 1 (Lungs)

Other hazards

GHS label elements

Hazard pictograms :



Signal Word : Danger

Safety Data Sheet
according to OSHA 1910.1200 Hazard Communication Standard



Sikacrete®-421 CI Rapid

Revision Date 07/18/2025

Print Date 07/18/2025

- Hazard Statements : H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H350 May cause cancer by inhalation.
H372 Causes damage to organs (Lungs) through prolonged or repeated exposure.
- Supplemental Hazard Statements : Corrosive to the respiratory tract.
- Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
- Response:**
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
- Storage:**
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
- Disposal:**
P501 Dispose of contents/ container to an approved waste disposal plant.



Sikacrete®-421 CI Rapid

Revision Date 07/18/2025

Print Date 07/18/2025

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration $\geq 1\%$.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Components

| Chemical name | CAS No./Unique ID | Classification | Concentration (% w/w) |
|----------------------------|-------------------|--|-----------------------|
| Quartz (SiO ₂) | 14808-60-7 | Carc. 1A; H350 STOT RE 1; H372 STOT SE 3; H335 | $\geq 30 - \leq 60$ |
| Limestone | 1317-65-3 | | $\geq 10 - \leq 30$ |
| Portland Cement | 65997-15-1 | Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 STOT SE 3; H335 | $\geq 10 - \leq 30$ |
| calcium sulfate, natural | 7778-18-9 | | $\geq 1 - \leq 5$ |
| fumes, silica | 69012-64-2 | | $\geq 0.5 - \leq 1.5$ |
| Cristobalite | 14464-46-1 | Carc. 1A; H350 | $\geq 0.1 - \leq 1$ |

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.



Sikacrete®-421 CI Rapid

Revision Date 07/18/2025

Print Date 07/18/2025

Do not induce vomiting without medical advice.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Take victim immediately to hospital.

Most important symptoms and effects, both acute and delayed : Prolonged exposure can cause silicosis.
May cause an allergic skin reaction.
Causes serious eye damage.
May cause respiratory irritation.
May cause cancer by inhalation.
Causes damage to organs through prolonged or repeated exposure.
Causes severe burns.
Corrosive to the respiratory tract.
Health injuries may be delayed.
corrosive effects
sensitizing effects
Allergic reactions
Dermatitis

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Hazardous combustion products : No hazardous combustion products are known

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Avoid breathing dust.
Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
Local authorities should be advised if significant spillages cannot be contained.



Sikacrete®-421 CI Rapid

Revision Date 07/18/2025

Print Date 07/18/2025

Methods and materials for containment and cleaning up : Pick up and arrange disposal without creating dust.
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Avoid dust formation.
Provide appropriate exhaust ventilation at places where dust is formed.

Advice on safe handling : Avoid formation of respirable particles.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products.

Conditions for safe storage : Store in original container.
Keep in a well-ventilated place.
Observe label precautions.
Store in accordance with local regulations.

Materials to avoid : Explosives
Oxidizing agents
Poisonous gases
Dangerous when wet
Flammable solids
Organic peroxides
Poisonous liquids
Spontaneously Combustible Substances

Further information on storage stability : Keep in a dry place.
No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|----------------------------|------------|-------------------------------|--|-------|
| Quartz (SiO ₂) | 14808-60-7 | TWA (Respirable par- | 0.025 mg/m ³ | ACGIH |

Safety Data Sheet
according to OSHA 1910.1200 Hazard Communication Standard



Sikacrete®-421 CI Rapid

Revision Date 07/18/2025

Print Date 07/18/2025

| | | | | |
|-----------------|------------|-------------------------------------|----------------------|-----------|
| | | ticulate matter) | | |
| | | TWA (Respirable dust) | 0.05 mg/m3 | OSHA Z-1 |
| | | TWA (respirable) | 10 mg/m3 / %SiO2+2 | OSHA Z-3 |
| | | TWA (respirable) | 250 mppcf / %SiO2+5 | OSHA Z-3 |
| | | TWA (respirable dust fraction) | 0.1 mg/m3 | OSHA P0 |
| | | TWA (Respirable particulate matter) | 0.025 mg/m3 (Silica) | ACGIH |
| | | PEL (respirable) | 0.05 mg/m3 | OSHA CARC |
| | | TWA (respirable dust fraction) | 0.1 mg/m3 | OSHA P0 |
| | | TWA (Respirable particulate matter) | 0.025 mg/m3 | ACGIH |
| | | TWA (Respirable particulate matter) | 0.025 mg/m3 (Silica) | ACGIH |
| Limestone | 1317-65-3 | TWA (total dust) | 15 mg/m3 | OSHA Z-1 |
| | | TWA (respirable fraction) | 5 mg/m3 | OSHA Z-1 |
| | | TWA (Total dust) | 15 mg/m3 | OSHA P0 |
| | | TWA (respirable dust fraction) | 5 mg/m3 | OSHA P0 |
| Portland Cement | 65997-15-1 | TWA (Respirable particulate matter) | 1 mg/m3 | ACGIH |
| | | TWA (total dust) | 15 mg/m3 | OSHA Z-1 |
| | | TWA (respirable fraction) | 5 mg/m3 | OSHA Z-1 |
| | | TWA (Total dust) | 10 mg/m3 | OSHA P0 |
| | | TWA (respirable dust fraction) | 5 mg/m3 | OSHA P0 |

Safety Data Sheet
according to OSHA 1910.1200 Hazard Communication Standard



Sikacrete®-421 CI Rapid

Revision Date 07/18/2025

Print Date 07/18/2025

| | | | | |
|--------------------------|------------|-------------------------------------|--|----------|
| | | TWA (Dust) | 50 Million particles per cubic foot | OSHA Z-3 |
| | | TWA (Total) | 10 mg/m3 | OSHA P0 |
| | | TWA (Respirable fraction) | 5 mg/m3 | OSHA P0 |
| calcium sulfate, natural | 7778-18-9 | TWA (total dust) | 15 mg/m3 | OSHA Z-1 |
| | | TWA (respirable fraction) | 5 mg/m3 | OSHA Z-1 |
| | | TWA (Total dust) | 15 mg/m3 | OSHA P0 |
| | | TWA (respirable dust fraction) | 5 mg/m3 | OSHA P0 |
| | | TWA (Inhalable particulate matter) | 10 mg/m3 (Calcium) | ACGIH |
| fumes, silica | 69012-64-2 | TWA (Dust) | 20 Million particles per cubic foot (Silica) | OSHA Z-3 |
| | | TWA (Dust) | 80 mg/m3 / %SiO2 (Silica) | OSHA Z-3 |
| | | TWA (Dust) | 20 Million particles per cubic foot (Silica) | OSHA Z-3 |
| | | TWA (Dust) | 80 mg/m3 / %SiO2 (Silica) | OSHA Z-3 |
| Cristobalite | 14464-46-1 | TWA (Respirable dust) | 0.05 mg/m3 | OSHA Z-1 |
| | | TWA (respirable dust fraction) | 0.05 mg/m3 | OSHA P0 |
| | | TWA (Respirable particulate matter) | 0.025 mg/m3 (Silica) | ACGIH |

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Particles of nuisance dust

| Form of exposure | Value type | Control parameters | Basis |
|---------------------|------------|--------------------|----------|
| total dust | TWA | 15 mg/m3 | OSHA Z-3 |
| respirable fraction | TWA | 5 mg/m3 | OSHA Z-3 |

Safety Data Sheet
according to OSHA 1910.1200 Hazard Communication Standard



Sikacrete®-421 CI Rapid

Revision Date 07/18/2025

Print Date 07/18/2025

- Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
- Personal protective equipment**
- Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
- The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product.
Remove contaminated clothing and protective equipment before entering eating areas.
Wash thoroughly after handling.
Avoid breathing dust.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : powder
- Color : gray
- Odor : odorless
- Odor Threshold : No data available
- pH : Not applicable

Safety Data Sheet
according to OSHA 1910.1200 Hazard Communication Standard



Sikacrete®-421 CI Rapid

Revision Date 07/18/2025

Print Date 07/18/2025

| | | |
|--|---|---|
| Melting point/ range / Freezing point | : | No data available |
| Boiling point/boiling range | : | No data available |
| Flash point | : | Not applicable |
| Evaporation rate | : | No data available |
| Flammability (solid, gas) | : | No data available |
| Upper explosion limit / Upper flammability limit | : | No data available |
| Lower explosion limit / Lower flammability limit | : | No data available |
| Vapor pressure | : | No data available |
| Relative vapor density | : | No data available |
| Density | : | ca. 2.3 g/cm ³ (73 °F / 23 °C) |
| Solubility(ies) | | |
| Water solubility | : | insoluble |
| Solubility in other solvents | : | No data available |
| Partition coefficient: n-octanol/water | : | No data available |
| Autoignition temperature | : | No data available |
| Decomposition temperature | : | No data available |
| Viscosity | | |
| Viscosity, dynamic | : | No data available |
| Viscosity, kinematic | : | Not applicable |
| Explosive properties | : | No data available |
| Oxidizing properties | : | No data available |
| Volatile organic compounds (VOC) content | : | Not applicable |

SECTION 10. STABILITY AND REACTIVITY

| | | |
|--------------------|---|---|
| Reactivity | : | No dangerous reaction known under conditions of normal use. |
| Chemical stability | : | The product is chemically stable. |

Safety Data Sheet
according to OSHA 1910.1200 Hazard Communication Standard



Sikacrete®-421 CI Rapid

Revision Date 07/18/2025

Print Date 07/18/2025

Possibility of hazardous reactions : Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Components:

calcium sulfate, natural:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

May cause cancer by inhalation.

| | | |
|-------------|--|------------|
| IARC | Group 1: Carcinogenic to humans Quartz (SiO ₂) (Silica dust, crystalline) | 14808-60-7 |
| | Group 1: Carcinogenic to humans cristobalite (Silica dust, crystalline) | 14464-46-1 |
| OSHA | OSHA specifically regulated carcinogen Quartz (SiO ₂) (crystalline silica) | 14808-60-7 |



Sikacrete®-421 CI Rapid

Revision Date 07/18/2025

Print Date 07/18/2025

| | | |
|------------|---|------------|
| NTP | Known to be human carcinogen Quartz (SiO ₂) (Silica, Crystalline (Respirable Size)) | 14808-60-7 |
| | Known to be human carcinogen cristobalite (Silica, Crystalline (Respirable Size)) | 14464-46-1 |

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

May cause respiratory irritation.
Corrosive to the respiratory tract.

STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure.
Prolonged exposure can cause silicosis.
Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Aspiration toxicity

Not classified due to lack of data.

Further information

Product:

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.

Safety Data Sheet
according to OSHA 1910.1200 Hazard Communication Standard



Sikacrete®-421 CI Rapid

Revision Date 07/18/2025

Print Date 07/18/2025

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Domestic regulation

49 CFR Road

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

- TSCA list** : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 304 Extremely Hazardous Substances Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

- SARA 311/312 Hazards** : Respiratory or skin sensitization

Safety Data Sheet
according to OSHA 1910.1200 Hazard Communication Standard



Sikacrete®-421 CI Rapid

Revision Date 07/18/2025

Print Date 07/18/2025

Carcinogenicity
Specific target organ toxicity (single or repeated exposure)
Skin corrosion or irritation
Serious eye damage or eye irritation

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

California Prop. 65

⚠ WARNING: This product can expose you to chemicals including Quartz (SiO₂), which is known to the State of California to cause cancer, and Portland Cement, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

| | |
|-----------------|--|
| ACGIH | : USA. ACGIH Threshold Limit Values (TLV) |
| OSHA CARC | : OSHA Specifically Regulated Chemicals/Carcinogens |
| OSHA P0 | : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values) |
| OSHA Z-1 | : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| OSHA Z-3 | : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts |
| ACGIH / TWA | : 8-hour, time-weighted average |
| OSHA CARC / PEL | : Permissible exposure limit (PEL) |
| OSHA P0 / TWA | : 8-hour time weighted average |
| OSHA Z-1 / TWA | : 8-hour time weighted average |
| OSHA Z-3 / TWA | : 8-hour time weighted average |

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

Safety Data Sheet
according to OSHA 1910.1200 Hazard Communication Standard



Sikacrete®-421 CI Rapid

Revision Date 07/18/2025

Print Date 07/18/2025

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 07/18/2025

100000015986
US / Z8