

## SAFETY DATA SHEET



## CAL BRONZE

Version 5.0      Revision Date: 09/24/2015      SDS Number: 118160-00006      Date of last issue: 09/04/2015  
 Date of first issue: 05/18/2015

## SECTION 1. IDENTIFICATION

Product name : CAL BRONZE

SDS-Identcode : 059G

**Manufacturer or supplier's details**

Company name of supplier : Bestolife Corporation

Address : 2777 N. Stemmons Frwy Ste 1800  
 Dallas TX 75207,

Telephone : 855-243-9164/972-865-8961

Telefax : 214-631-3047

Emergency telephone : CHEMTREC U.S.: 800-424-9300, International 703-527-3887  
 (24-hours/7 days)

E-mail address : www.bestolife.com

**Recommended use of the chemical and restrictions on use**

Recommended use : Industrial use  
 Thread Compound (Pipe Dope) and Jacking grease for use in  
 Offshore industries  
 Mining, (without offshore industries)

Restrictions on use : Do not use on oxygen lines or in oxygen enriched  
 atmospheres.

## SECTION 2. HAZARDS IDENTIFICATION

**GHS Classification**

Eye irritation : Category 2A

Carcinogenicity : Category 2

Reproductive toxicity : Category 1A

Specific target organ  
 systemic toxicity - repeated  
 exposure : Category 1 (Kidney, Central nervous system, Blood)

**GHS Label element**

SAFETY DATA SHEET



**CAL BRONZE**

Version 5.0      Revision Date: 09/24/2015      SDS Number: 118160-00006      Date of last issue: 09/04/2015  
 Date of first issue: 05/18/2015

Hazard pictograms :

Signal Word : Danger

Hazard Statements : H319 Causes serious eye irritation.  
 H351 Suspected of causing cancer.  
 H360 May damage fertility or the unborn child.  
 H372 Causes damage to organs (Kidney, Central nervous system, Blood) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**  
 P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.  
 P264 Wash skin thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
**Response:**  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
 P337 + P313 If eye irritation persists: Get medical advice/ attention.  
**Storage:**  
 P405 Store locked up.  
**Disposal:**  
 P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**  
 None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous ingredients**

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 30 - < 50
Talc	14807-96-6	>= 20 - < 30
Graphite	7782-42-5	>= 10 - < 20
Lead	7439-92-1	>= 10 - < 20
Copper metal powder	7440-50-8	>= 1 - < 5
12-Hydroxy lithium stearate	7620-77-1	>= 1 - < 5

SAFETY DATA SHEET



**CAL BRONZE**

Version 5.0      Revision Date: 09/24/2015      SDS Number: 118160-00006      Date of last issue: 09/04/2015  
 Date of first issue: 05/18/2015

Calcium oxide	1305-78-8	>= 1 - < 5
Quartz	14808-60-7	>= 0.1 - < 1

**SECTION 4. FIRST AID MEASURES**

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes serious eye irritation.  
Suspected of causing cancer.  
May damage fertility or the unborn child.  
Causes damage to organs through prolonged or repeated exposure.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
- Notes to physician : Treat symptomatically and supportively.

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO2)  
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.

**SAFETY DATA SHEET**



**CAL BRONZE**

Version 5.0	Revision Date: 09/24/2015	SDS Number: 118160-00006	Date of last issue: 09/04/2015 Date of first issue: 05/18/2015
----------------	------------------------------	-----------------------------	---

- Hazardous combustion products : Carbon oxides  
Lead compounds  
Metal oxides
  
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
  
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Follow safe handling advice and personal protective equipment recommendations.
  
- Environmental precautions : Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
  
- Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

**SECTION 7. HANDLING AND STORAGE**

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
  
- Advice on safe handling : Do not get on skin or clothing.  
Do not swallow.  
Do not get in eyes.  
Handle in accordance with good industrial hygiene and safety practice.  
Keep container tightly closed.  
Keep away from water.  
Protect from moisture.  
Take care to prevent spills, waste and minimize release to the environment.
  
- Conditions for safe storage : Keep in properly labeled containers.

SAFETY DATA SHEET



**CAL BRONZE**

Version 5.0      Revision Date: 09/24/2015      SDS Number: 118160-00006      Date of last issue: 09/04/2015  
 Date of first issue: 05/18/2015

Store locked up.  
 Keep tightly closed.  
 Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:  
 Strong oxidizing agents  
 Organic peroxides  
 Explosives  
 Gases

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Ingredients with workplace control parameters**

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Talc	14807-96-6	TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	2 mg/m3	NIOSH REL
		TWA (Respirable fraction)	2 mg/m3	ACGIH
Graphite	7782-42-5	TWA (Respirable)	2.5 mg/m3	NIOSH REL
		TWA (Respirable fraction)	2 mg/m3	ACGIH
		TWA (Dust)	15 Million particles per cubic foot	OSHA Z-3
Lead	7439-92-1	TWA	0.05 mg/m3 (Lead)	NIOSH REL
		TWA	0.05 mg/m3 (Lead)	ACGIH
		PEL	0.05 mg/m3 (Lead)	OSHA CARC
Copper metal powder	7440-50-8	TWA (Dust and mist)	1 mg/m3 (Copper)	ACGIH
		TWA (Fumes)	0.2 mg/m3 (Copper)	ACGIH
		TWA (Dust)	1 mg/m3 (Copper)	NIOSH REL
		TWA (Mist)	1 mg/m3 (Copper)	NIOSH REL

SAFETY DATA SHEET



**CAL BRONZE**

Version 5.0      Revision Date: 09/24/2015      SDS Number: 118160-00006      Date of last issue: 09/04/2015  
 Date of first issue: 05/18/2015

		TWA (dusts and mists)	1 mg/m3 (Copper)	OSHA Z-1
		TWA (Fumes)	0.1 mg/m3 (Copper)	OSHA Z-1
12-Hydroxy lithium stearate	7620-77-1	TWA	10 mg/m3	ACGIH
Calcium oxide	1305-78-8	TWA	2 mg/m3	ACGIH
		TWA	2 mg/m3	NIOSH REL
		TWA	5 mg/m3	OSHA Z-1
Quartz	14808-60-7	TWA (total dust)	30 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (Respirable fraction)	0.025 mg/m3 (Silica)	ACGIH
		TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL

**Occupational exposure limits of decomposition products**

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Calcium hydroxide	1305-62-0	TWA	5 mg/m3	ACGIH
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA	5 mg/m3	NIOSH REL

**Biological occupational exposure limits**

Ingredients	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Lead	7439-92-1	Lead (Lead)	In blood	Not critical	30 µg/ 100 ml	ACGIH BEI

**Engineering measures**

: Processing may form hazardous compounds (see section 10).  
 Minimize workplace exposure concentrations.  
 Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m3 - total dust, 5 mg/m3 - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m3 - respirable particles, 10 mg/m3 - inhalable particles.

**Personal protective equipment**

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where

SAFETY DATA SHEET



**CAL BRONZE**

Version 5.0	Revision Date: 09/24/2015	SDS Number: 118160-00006	Date of last issue: 09/04/2015 Date of first issue: 05/18/2015
----------------	------------------------------	-----------------------------	---

concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

- Hand protection Material : Impervious gloves
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment: Safety goggles
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : Viscous semi-solid
- Color : copper
- Odor : Petroleum
- Odor Threshold : No data available
- pH : Not applicable (not an aqueous solution)
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : No data available

## SAFETY DATA SHEET



## CAL BRONZE

Version	Revision Date:	SDS Number:	Date of last issue:
5.0	09/24/2015	118160-00006	09/04/2015
			Date of first issue: 05/18/2015

Flash point	: No data available
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapor pressure	: No data available
Relative vapor density	: No data available
Relative density	: 1.4
Density	: No data available
Solubility(ies)	
Water solubility	: negligible
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: No data available
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Molecular weight	: No data available

## SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Can react with strong oxidizing agents. Hazardous decomposition products will be formed upon contact with water or humid air.
Conditions to avoid	: Exposure to moisture.
Incompatible materials	: Oxidizing agents

## SAFETY DATA SHEET



## CAL BRONZE

Version 5.0      Revision Date: 09/24/2015      SDS Number: 118160-00006      Date of last issue: 09/04/2015  
Date of first issue: 05/18/2015

Water

Hazardous decomposition products  
Contact with water or humid air : Calcium hydroxide

## SECTION 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure**

Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Ingredients:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Method: OECD Test Guideline 402  
Remarks: Based on data from similar materials

**Talc:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Remarks: Based on data from similar materials

**Graphite:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 401  
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 2 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity

**Lead:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Remarks: Based on data from similar materials

## SAFETY DATA SHEET



## CAL BRONZE

Version 5.0      Revision Date: 09/24/2015      SDS Number: 118160-00006      Date of last issue: 09/04/2015  
 Date of first issue: 05/18/2015

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
 Remarks: Based on data from similar materials

**Copper metal powder:**

Acute oral toxicity : LD50 (Rat): > 2,500 mg/kg  
 Method: OECD Test Guideline 423  
 Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 5.11 mg/l  
 Exposure time: 4 h  
 Test atmosphere: dust/mist  
 Method: OECD Test Guideline 436  
 Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
 Method: OECD Test Guideline 402  
 Assessment: The substance or mixture has no acute dermal toxicity

**12-Hydroxy lithium stearate:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
 Assessment: The substance or mixture has no acute oral toxicity

**Calcium oxide:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
 Method: OECD Test Guideline 425  
 Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,500 mg/kg  
 Method: OECD Test Guideline 402  
 Assessment: The substance or mixture has no acute dermal toxicity  
 Remarks: Based on data from similar materials

**Quartz:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

**Skin corrosion/irritation**

Not classified based on available information.

**Ingredients:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Species: Rabbit  
 Result: No skin irritation  
 Remarks: Based on data from similar materials

**Talc:**

Species: Rabbit  
 Result: No skin irritation

## SAFETY DATA SHEET



## CAL BRONZE

Version 5.0      Revision Date: 09/24/2015      SDS Number: 118160-00006      Date of last issue: 09/04/2015  
 Date of first issue: 05/18/2015

**Graphite:**

Species: Rabbit  
 Method: OECD Test Guideline 404  
 Result: No skin irritation

**Lead:**

Species: Rabbit  
 Method: OECD Test Guideline 404  
 Result: No skin irritation  
 Remarks: Based on data from similar materials

**Copper metal powder:**

Species: Rabbit  
 Method: OECD Test Guideline 404  
 Result: No skin irritation

**12-Hydroxy lithium stearate:**

Species: Rabbit  
 Result: No skin irritation  
 Remarks: Based on data from similar materials

**Calcium oxide:**

Species: Rabbit  
 Method: OECD Test Guideline 404  
 Result: Skin irritation  
 Remarks: Based on data from similar materials

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Ingredients:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Species: Rabbit  
 Result: No eye irritation  
 Remarks: Based on data from similar materials

**Talc:**

Species: Rabbit  
 Result: No eye irritation

**Graphite:**

Species: Rabbit  
 Result: No eye irritation

**Lead:**

Species: Rabbit  
 Result: No eye irritation  
 Method: OECD Test Guideline 405  
 Remarks: Based on data from similar materials

**Copper metal powder:**

Species: Rabbit  
 Result: No eye irritation  
 Method: OECD Test Guideline 405

## SAFETY DATA SHEET



## CAL BRONZE

Version 5.0      Revision Date: 09/24/2015      SDS Number: 118160-00006      Date of last issue: 09/04/2015  
 Date of first issue: 05/18/2015

**12-Hydroxy lithium stearate:**

Species: Rabbit  
 Result: No eye irritation  
 Remarks: Based on data from similar materials

**Calcium oxide:**

Species: Rabbit  
 Result: Irreversible effects on the eye  
 Method: OECD Test Guideline 405

**Respiratory or skin sensitization**

Skin sensitization: Not classified based on available information.  
 Respiratory sensitization: Not classified based on available information.

**Ingredients:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Test Type: Buehler Test  
 Routes of exposure: Skin contact  
 Species: Guinea pig  
 Result: negative  
 Remarks: Based on data from similar materials

**Talc:**

Routes of exposure: Skin contact  
 Species: Humans  
 Result: negative

**Graphite:**

Test Type: Local lymph node assay (LLNA)  
 Routes of exposure: Skin contact  
 Species: Mouse  
 Result: negative

**Lead:**

Test Type: Maximization Test  
 Routes of exposure: Skin contact  
 Species: Guinea pig  
 Method: OECD Test Guideline 406  
 Result: negative  
 Remarks: Based on data from similar materials

**Copper metal powder:**

Test Type: Maximization Test  
 Routes of exposure: Skin contact  
 Species: Guinea pig  
 Method: OECD Test Guideline 406  
 Result: negative

**12-Hydroxy lithium stearate:**

Test Type: Local lymph node assay (LLNA)  
 Routes of exposure: Skin contact  
 Species: Mouse  
 Method: OECD Test Guideline 429  
 Result: negative

SAFETY DATA SHEET



**CAL BRONZE**

Version 5.0      Revision Date: 09/24/2015      SDS Number: 118160-00006      Date of last issue: 09/04/2015  
 Date of first issue: 05/18/2015

**Germ cell mutagenicity**

Not classified based on available information.

**Ingredients:**

**Distillates (petroleum), hydrotreated heavy naphthenic:**

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
 Method: OECD Test Guideline 471  
 Result: negative
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
 Species: Mouse  
 Application Route: Intraperitoneal injection  
 Method: OECD Test Guideline 474  
 Result: negative  
 Remarks: Based on data from similar materials

**Talc:**

- Genotoxicity in vitro : Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)  
 Result: negative
- Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro  
 Species: Rat  
 Application Route: Ingestion  
 Result: negative

**Graphite:**

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
 Result: negative

**Lead:**

- Genotoxicity in vitro : Test Type: In vitro sister chromatid exchange assay in mammalian cells  
 Result: negative  
 Remarks: Based on data from similar materials
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
 Species: Rat  
 Application Route: Ingestion  
 Result: positive  
 Remarks: Based on data from similar materials

**Copper metal powder:**

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
 Method: OECD Test Guideline 471  
 Result: negative
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
 Species: Mouse  
 Application Route: Ingestion  
 Method: Directive 67/548/EEC, Annex V, B.12.  
 Result: negative

## SAFETY DATA SHEET



## CAL BRONZE

Version 5.0      Revision Date: 09/24/2015      SDS Number: 118160-00006      Date of last issue: 09/04/2015  
 Date of first issue: 05/18/2015

Remarks: Based on data from similar materials

**Calcium oxide:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
 Method: OECD Test Guideline 471  
 Result: negative

**Carcinogenicity**

Suspected of causing cancer.

**Product:**

Carcinogenicity - Assessment : Petroleum distillates have been classified as not carcinogenic based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).

**Ingredients:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Species: Mouse  
 Application Route: Skin contact  
 Exposure time: 78 weeks  
 Method: OECD Test Guideline 451  
 Result: negative

**Talc:**

Species: Mouse  
 Application Route: inhalation (dust/mist/fume)  
 Exposure time: 2 Years  
 Result: negative

**Lead:**

Species: Rat  
 Application Route: Ingestion  
 Exposure time: 2 Years  
 Result: positive  
 Remarks: Based on data from similar materials

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

**Calcium oxide:**

Species: Rat  
 Application Route: Ingestion  
 Exposure time: 104 weeks  
 Result: negative  
 Remarks: Based on data from similar materials

**Quartz:**

Species: Humans  
 Application Route: inhalation (dust/mist/fume)  
 Result: positive  
 Remarks: IARC (International Agency for Research on Cancer)  
 The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

SAFETY DATA SHEET



**CAL BRONZE**

Version 5.0      Revision Date: 09/24/2015      SDS Number: 118160-00006      Date of last issue: 09/04/2015  
 Date of first issue: 05/18/2015

**Carcinogenicity - Assessment** : Positive evidence from human epidemiological studies (inhalation)

**IARC**

Group 1: Carcinogenic to humans

Quartz 14808-60-7

Group 2B: Possibly carcinogenic to humans

Lead 7439-92-1

**OSHA**

OSHA specifically regulated carcinogen

Lead 7439-92-1

**NTP**

Known to be human carcinogen

Quartz 14808-60-7

Reasonably anticipated to be a human carcinogen

Lead 7439-92-1

**Reproductive toxicity**

May damage fertility or the unborn child.

**Ingredients:**

**Talc:**

Effects on fetal development : Test Type: Embryo-fetal development  
 Species: Rat  
 Application Route: Ingestion  
 Result: negative

**Graphite:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
 Species: Rat  
 Application Route: Ingestion  
 Method: OECD Test Guideline 422  
 Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
 Species: Rat  
 Application Route: Ingestion  
 Method: OECD Test Guideline 422  
 Result: negative

**Lead:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
 Species: Mouse  
 Application Route: Ingestion  
 Result: positive  
 Remarks: Based on data from similar materials

## SAFETY DATA SHEET



## CAL BRONZE

Version 5.0      Revision Date: 09/24/2015      SDS Number: 118160-00006      Date of last issue: 09/04/2015  
 Date of first issue: 05/18/2015

Effects on fetal development : Test Type: Embryo-fetal development  
 Species: Rat  
 Application Route: Ingestion  
 Result: positive  
 Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Positive evidence of adverse effects on sexual function and fertility from human epidemiological studies., Positive evidence of adverse effects on development from human epidemiological studies.

**Copper metal powder:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
 Species: Rat  
 Application Route: Ingestion  
 Result: negative  
 Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
 Species: Rabbit  
 Application Route: Ingestion  
 Result: negative

**Calcium oxide:**

Effects on fetal development : Test Type: Embryo-fetal development  
 Species: Mouse  
 Application Route: Ingestion  
 Method: OECD Test Guideline 414  
 Result: negative

**STOT-single exposure**

Not classified based on available information.

**Ingredients:****Calcium oxide:**

Assessment: May cause respiratory irritation.

**STOT-repeated exposure**

Causes damage to organs (Kidney, Central nervous system, Blood) through prolonged or repeated exposure.

**Ingredients:****Lead:**

Target Organs: Kidney, Central nervous system, Blood

Assessment: Causes damage to organs through prolonged or repeated exposure.

**12-Hydroxy lithium stearate:**

Routes of exposure: Ingestion

Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

**Quartz:**

Routes of exposure: inhalation (dust/mist/fume)

Target Organs: Lungs

## SAFETY DATA SHEET



## CAL BRONZE

Version 5.0      Revision Date: 09/24/2015      SDS Number: 118160-00006      Date of last issue: 09/04/2015  
 Date of first issue: 05/18/2015

Assessment: Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

**Repeated dose toxicity****Ingredients:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Species: Rat  
 NOAEL: > 0.98 mg/l  
 Application Route: inhalation (dust/mist/fume)  
 Exposure time: 28 Days  
 Remarks: Based on data from similar materials

**Graphite:**

Species: Rat  
 NOAEL: 12 mg/m3  
 Application Route: inhalation (dust/mist/fume)  
 Exposure time: 28 Days  
 Method: OECD Test Guideline 412

**Lead:**

Species: Rat  
 NOAEL: 0.0015 mg/kg  
 LOAEL: 0.005 mg/kg  
 Application Route: Ingestion  
 Exposure time: 6 - 12 Months  
 Remarks: Based on data from similar materials

**Copper metal powder:**

Species: Rat  
 NOAEL:  $\geq$  2 mg/m3  
 Application Route: inhalation (dust/mist/fume)  
 Exposure time: 28 Days

**12-Hydroxy lithium stearate:**

Species: Rat  
 NOAEL: > 88 mg/kg  
 Application Route: Ingestion  
 Exposure time: 90 Days

**Quartz:**

Species: Humans  
 LOAEL: 0.053 mg/m3  
 Application Route: inhalation (dust/mist/fume)  
 Remarks: The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

**Aspiration toxicity**

Not classified based on available information.

## SAFETY DATA SHEET



## CAL BRONZE

Version 5.0      Revision Date: 09/24/2015      SDS Number: 118160-00006      Date of last issue: 09/04/2015  
Date of first issue: 05/18/2015

## SECTION 12. ECOLOGICAL INFORMATION

## Ecotoxicity

**Ingredients:****Distillates (petroleum), hydrotreated heavy naphthenic:**

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Remarks: Based on data from similar materials
- Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l  
Exposure time: 21 d  
Remarks: Based on data from similar materials
- Toxicity to bacteria : NOEC: > 1.93 mg/l  
Exposure time: 10 min  
Remarks: Based on data from similar materials

**Talc:**

- Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100,000 mg/l  
Exposure time: 24 h

**Graphite:**

- Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202
- Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201
- Toxicity to bacteria : EC50: > 1,012.5 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

**Lead:**

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.107 mg/l  
Exposure time: 96 h

SAFETY DATA SHEET



**CAL BRONZE**

Version 5.0      Revision Date: 09/24/2015      SDS Number: 118160-00006      Date of last issue: 09/04/2015  
 Date of first issue: 05/18/2015

	Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Ceriodaphnia dubia (water flea)): 0.029 mg/l Exposure time: 48 h Remarks: Based on data from similar materials
Toxicity to algae	: ErC50 (Pseudokirchneriella subcapitata (green algae)): 0.025 mg/l Exposure time: 72 h Remarks: Based on data from similar materials
	EC10 (Pseudokirchneriella subcapitata (green algae)): 6.1 µg/l Exposure time: 72 h Remarks: Based on data from similar materials
M-Factor (Acute aquatic toxicity)	: 10
Toxicity to fish (Chronic toxicity)	: EC10 (Pimephales promelas (fathead minnow)): 20 µg/l Exposure time: 30 d Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: EC10 (Ceriodaphnia dubia (water flea)): 1.7 µg/l Exposure time: 7 d Remarks: Based on data from similar materials
M-Factor (Chronic aquatic toxicity)	: 10
<b>Copper metal powder:</b>	
Toxicity to fish	: LC50: 10 - < 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: LC50 (Ceriodaphnia dubia (water flea)): 66 mg/l Exposure time: 48 h Remarks: Based on data from similar materials
Toxicity to algae	: ErC50 (Pseudokirchneriella subcapitata (green algae)): 30 - 824 µg/l Exposure time: 72 h Remarks: Based on data from similar materials
M-Factor (Acute aquatic toxicity)	: 10
Toxicity to fish (Chronic toxicity)	: NOEC: > 1 - 10 µg/l
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 21.5 - 181 µg/l Exposure time: 21 d Remarks: Based on data from similar materials
M-Factor (Chronic aquatic toxicity)	: 10

SAFETY DATA SHEET



**CAL BRONZE**

Version 5.0      Revision Date: 09/24/2015      SDS Number: 118160-00006      Date of last issue: 09/04/2015  
 Date of first issue: 05/18/2015

**12-Hydroxy lithium stearate:**

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
 Exposure time: 96 h  
 Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l  
 Exposure time: 48 h  
 Method: OECD Test Guideline 202
- Toxicity to algae : NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
 Exposure time: 72 h  
 Method: OECD Test Guideline 201

**Calcium oxide:**

- Toxicity to fish : LC50 (Gasterosteus aculeatus (threespine stickleback)): 457 mg/l  
 Exposure time: 96 h  
 Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : LC50: 158 mg/l  
 Exposure time: 96 h  
 Remarks: Based on data from similar materials
- Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 184.57 mg/l  
 Exposure time: 72 h  
 Method: OECD Test Guideline 201  
 Remarks: Based on data from similar materials
- NOEC (Pseudokirchneriella subcapitata (green algae)): 48 mg/l  
 Exposure time: 72 h  
 Method: OECD Test Guideline 201  
 Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 32 mg/l  
 Exposure time: 12 d  
 Remarks: Based on data from similar materials
- Toxicity to bacteria : EC50: 300.4 mg/l  
 Exposure time: 3 h  
 Method: OECD Test Guideline 209  
 Remarks: Based on data from similar materials

**Quartz:**

- Ecotoxicology Assessment
- Acute aquatic toxicity : No toxicity at the limit of solubility.
- Chronic aquatic toxicity : No toxicity at the limit of solubility.

**Persistence and degradability**

**Ingredients:**

SAFETY DATA SHEET



**CAL BRONZE**

Version 5.0      Revision Date: 09/24/2015      SDS Number: 118160-00006      Date of last issue: 09/04/2015  
 Date of first issue: 05/18/2015

**Distillates (petroleum), hydrotreated heavy naphthenic:**

Biodegradability : Result: Not readily biodegradable.  
 Biodegradation: 2 - 4 %  
 Exposure time: 28 d  
 Method: OECD Test Guideline 301B

**12-Hydroxy lithium stearate:**

Biodegradability : Result: Readily biodegradable.  
 Biodegradation: 78 %  
 Exposure time: 28 d  
 Method: OECD Test Guideline 301C

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.  
 Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
 If not otherwise specified: Dispose of as unused product.

**SECTION 14. TRANSPORT INFORMATION**

**International Regulation**

**UNRTDG**

UN number : UN 3077  
 Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Lead, Copper metal powder)  
 Class : 9  
 Packing group : III  
 Labels : 9

**IATA-DGR**

UN/ID No. : UN 3077  
 Proper shipping name : Environmentally hazardous substance, solid, n.o.s. (Lead, Copper metal powder)  
 Class : 9  
 Packing group : III  
 Labels : Miscellaneous  
 Packing instruction (cargo) : 956

SAFETY DATA SHEET



**CAL BRONZE**

Version 5.0      Revision Date: 09/24/2015      SDS Number: 118160-00006      Date of last issue: 09/04/2015  
 Date of first issue: 05/18/2015

aircraft)  
 Packing instruction (passenger aircraft) : 956

**IMDG-Code**

UN number : UN 3077  
 Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Lead, Copper metal powder)  
 Class : 9  
 Packing group : III  
 Labels : 9  
 EmS Code : F-A, S-F  
 Marine pollutant : yes

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation**

**49 CFR**

UN/ID/NA number : UN 3077  
 Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Lead, Copper metal powder)  
 Class : 9  
 Packing group : III  
 Labels : CLASS 9  
 ERG Code : 171  
 Marine pollutant : yes (Lead, Copper metal powder)  
 Remarks : THE ABOVE INFORMATION ONLY APPLIES TO PACKAGE SIZES WHERE THE HAZARDOUS SUBSTANCE MEETS THE REPORTABLE QUANTITY.

**SECTION 15. REGULATORY INFORMATION**

**EPCRA - Emergency Planning and Community Right-to-Know**

**CERCLA Reportable Quantity**

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Zinc	7440-66-6	1000	20658
Lead	7439-92-1	10	93
Copper metal powder	7440-50-8	5000	172123

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Acute Health Hazard  
 Chronic Health Hazard

SAFETY DATA SHEET



**CAL BRONZE**

Version 5.0      Revision Date: 09/24/2015      SDS Number: 118160-00006      Date of last issue: 09/04/2015  
 Date of first issue: 05/18/2015

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Zinc	7440-66-6	4.8408 %
Copper metal powder	7440-50-8	2.9049 %

**US State Regulations**

**Pennsylvania Right To Know**

Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	30 - 50 %
Talc	14807-96-6	20 - 30 %
Graphite	7782-42-5	10 - 20 %
Lead	7439-92-1	10 - 20 %
Zinc	7440-66-6	1 - 5 %
Copper metal powder	7440-50-8	1 - 5 %
Calcium oxide	1305-78-8	1 - 5 %
Zinc oxide	1314-13-2	0.1 - 1 %
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	0 - 0.1 %
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	0 - 0.1 %
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5	0 - 0.1 %

**New Jersey Right To Know**

Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	30 - 50 %
Talc	14807-96-6	20 - 30 %
Graphite	7782-42-5	10 - 20 %
Lead	7439-92-1	10 - 20 %
Zinc	7440-66-6	1 - 5 %
Copper metal powder	7440-50-8	1 - 5 %
Calcium oxide	1305-78-8	1 - 5 %
Quartz	14808-60-7	0.1 - 1 %

**California Prop. 65**

WARNING! This product contains a chemical known in the State of California to cause cancer.

Lead	7439-92-1
Quartz	14808-60-7
Cadmium	7440-43-9

WARNING: This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

Lead	7439-92-1
Cadmium	7440-43-9

**The ingredients of this product are reported in the following inventories:**

DSL : All components of this product are on the Canadian DSL

SAFETY DATA SHEET



**CAL BRONZE**


Version 5.0      Revision Date: 09/24/2015      SDS Number: 118160-00006      Date of last issue: 09/04/2015  
 Date of first issue: 05/18/2015

TSCA : All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

**SECTION 16. OTHER INFORMATION**

**Further information**

**NFPA:**



**HMIS III:**

HEALTH	2*
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight, 2 = Moderate, 3 = High, 4 = Extreme, \* = Chronic

**Full text of other abbreviations**

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
- ACGIH / TWA : 8-hour, time-weighted average
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
- OSHA CARC / PEL : Permissible exposure limit (PEL)
- OSHA Z-1 / TWA : 8-hour time weighted average
- OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association

## SAFETY DATA SHEET



## CAL BRONZE

Version	Revision Date:	SDS Number:	Date of last issue: 09/04/2015
5.0	09/24/2015	118160-00006	Date of first issue: 05/18/2015

tion; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 09/24/2015

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8