



ULTRABOND® 1300 PART A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 2/21/2024 Revision date: 3/13/2024 Supersedes: 3/4/2024 Version: 4.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : ULTRABOND® 1300 PART A

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Adhesives Technology Corporation
450 East Copans Road
Pompano Beach, Florida 33064
USA
T (800) 892-1880 - F (800) 362-3320
www.atcepoxy.com

1.4. Emergency telephone number

Emergency number : 800-255-3924
Operating hours 24 hours / 24 hours, 7 days a week

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2	H319	Causes serious eye irritation
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Hazardous to the aquatic environment – Acute Hazard Category 2	H401	Toxic to aquatic life
Hazardous to the aquatic environment – Chronic Hazard Category 2	H411	Toxic to aquatic life with long lasting effects

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US)

: Warning

Hazard statements (GHS US)

: H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H401 - Toxic to aquatic life
H411 - Toxic to aquatic life with long lasting effects
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 - If on skin: Wash with plenty of water.

Precautionary statements (GHS US)

ULTRABOND® 1300 PART A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P321 - Specific treatment (see supplemental first aid instruction on this label).
 P332+P313 - If skin irritation occurs: Get medical advice/attention.
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
 P337+P313 - If eye irritation persists: Get medical advice/attention.
 P362+P364 - Take off contaminated clothing and wash it before reuse.
 P363 - Wash contaminated clothing before reuse.
 P391 - Collect spillage.
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Bisphenol A diglycidyl ether resin	CAS-No.: 1675-54-3	≥ 60	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Oxirane, 2-[(C12-14-alkyloxy)methyl] derivs.	CAS-No.: 68609-97-2	≥ 1	Skin Irrit. 2, H315 Skin Sens. 1, H317
Titanium oxide (TiO ₂)	CAS-No.: 13463-67-7	< 1	Carc. 2, H351

Comments : This product contains Titanium Dioxide, which is suspected of causing cancer when inhaled in fine particulate form. Titanium Dioxide should not be respirable in this formulation.

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
 First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
 First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
 First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.
 Symptoms/effects after eye contact : Eye irritation.

ULTRABOND® 1300 PART A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Mechanically recover the product.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapors/spray.
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

ULTRABOND® 1300 PART A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ULTRABOND® 1300 PART A

No additional information available

Oxirane, 2-[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

No additional information available

Titanium oxide (TiO₂) (13463-67-7)

USA - ACGIH - Occupational Exposure Limits

Local name	Titanium dioxide (*not respirable as contained in this liquid mixture)
ACGIH OEL TWA	0.2 mg/m ³ (Respirable fraction) 2.5 mg/m ³ (Respirable fraction)
Remark (ACGIH)	TLV® Basis: LRT irr; pneumoconiosis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2022

USA - OSHA - Occupational Exposure Limits

Local name	Titanium dioxide (*not respirable as contained in this liquid mixture)
------------	--

Bisphenol A diglycidyl ether resin (1675-54-3)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



ULTRABOND® 1300 PART A**Safety Data Sheet**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	: Solid
Color	: Mixture contains one or more component(s) which have the following colour(s): Colourless Pure substance: white Unpurified: coloured White Colourless to white Yellow-brown
Odor	: There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour: Mild odour Characteristic odour Odourless
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: No data available
Flash point	: Not applicable
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: No data available
Explosion limits	: Not applicable
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity**10.1. Reactivity**

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

ULTRABOND® 1300 PART A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Oxirane, 2-[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

LD50 oral rat	26800 mg/kg body weight (Rat, Male, Experimental value, Oral, 14 day(s))
LD50 oral	17100 mg/kg
ATE US (oral)	17100 mg/kg body weight

Titanium oxide (TiO2) (13463-67-7)

LD50 oral rat	> 2000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 oral	5000 mg/kg
LC50 Inhalation - Rat	> 5.09 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male, Experimental value, Inhalation (dust), 14 day(s))
LC50 Inhalation - Rat (Dust/Mist)	> 3.43 mg/l Source: ECHA
ATE US (oral)	5000 mg/kg body weight

Bisphenol A diglycidyl ether resin (1675-54-3)

LD50 oral rat	> 2000 mg/kg body weight (OECD 420: Acute Oral toxicity – Acute Toxic Class Method, Rat, Female, Experimental value, Oral, 14 day(s))
LD50 oral	22736 mg/kg
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LD50 dermal	23200 mg/kg
ATE US (oral)	22736 mg/kg body weight
ATE US (dermal)	23200 mg/kg body weight

Skin corrosion/irritation : Causes skin irritation.

Oxirane, 2-[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

pH	No data available in the literature
----	-------------------------------------

Titanium oxide (TiO2) (13463-67-7)

pH	7 (aqueous suspension, 10 %)
----	------------------------------

Bisphenol A diglycidyl ether resin (1675-54-3)

pH	No data available in the literature
----	-------------------------------------

Serious eye damage/irritation : Causes serious eye irritation.

Oxirane, 2-[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

pH	No data available in the literature
----	-------------------------------------

Titanium oxide (TiO2) (13463-67-7)

pH	7 (aqueous suspension, 10 %)
----	------------------------------

ULTRABOND® 1300 PART A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Bisphenol A diglycidyl ether resin (1675-54-3)	
pH	No data available in the literature
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified.
Titanium oxide (TiO₂) (13463-67-7)	
Additional information	*Not a respirable hazard as contained in this liquid mixture
IARC group	2B - Possibly carcinogenic to humans
Bisphenol A diglycidyl ether resin (1675-54-3)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: Not applicable
Oxirane, 2-[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)	
Viscosity, kinematic	No data available in the literature
Titanium oxide (TiO₂) (13463-67-7)	
Viscosity, kinematic	Not applicable (solid)
Bisphenol A diglycidyl ether resin (1675-54-3)	
Viscosity, kinematic	No data available in the literature
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Titanium oxide (TiO₂) (13463-67-7)	
LC50 - Fish [1]	> 1000 mg/l (Pisces, Fresh water)
EC50 - Crustacea [1]	> 1000 mg/l (Invertebrata, Fresh water)
EC50 72h - Algae [1]	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)
Bisphenol A diglycidyl ether resin (1675-54-3)	
EC50 - Crustacea [1]	1.7 mg/l

12.2. Persistence and degradability

Oxirane, 2-[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)	
Not rapidly degradable	
Persistence and degradability	Readily biodegradable in water.

ULTRABOND® 1300 PART A**Safety Data Sheet**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Titanium oxide (TiO₂) (13463-67-7)	
Not rapidly degradable	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
Bisphenol A diglycidyl ether resin (1675-54-3)	
Not rapidly degradable	
Persistence and degradability	Not readily biodegradable in water.
12.3. Bioaccumulative potential	
Oxirane, 2-[[C12-14-alkyloxy)methyl] derivs. (68609-97-2)	
BCF - Fish [1]	160 – 263 (BCFWIN, Estimated value)
Partition coefficient n-octanol/water (Log Pow)	3.77 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Titanium oxide (TiO₂) (13463-67-7)	
Bioaccumulative potential	Not bioaccumulative.
Bisphenol A diglycidyl ether resin (1675-54-3)	
BCF - Other aquatic organisms [1]	31 (QSAR, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	≥ 2.918 (Experimental value, EU Method A.8: Partition Coefficient, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
12.4. Mobility in soil	
Oxirane, 2-[[C12-14-alkyloxy)methyl] derivs. (68609-97-2)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	> 5.63 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
Ecology - soil	Adsorbs into the soil.
Titanium oxide (TiO₂) (13463-67-7)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for mobility in soil.
Bisphenol A diglycidyl ether resin (1675-54-3)	
Surface tension	58.7 – 58.9 mN/m (20 °C, EU Method A.5: Surface tension)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.65 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Ecology - soil	Low potential for adsorption in soil.
12.5. Other adverse effects	
No additional information available	

ULTRABOND® 1300 PART A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
Not applicable	UN3077	3077	3077
14.2. Proper Shipping Name			
Not applicable	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Bisphenol A diglycidyl ether resin)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Bisphenol A diglycidyl ether resin)	Environmentally hazardous substance, solid, n.o.s. (Bisphenol A diglycidyl ether resin)
14.3. Transport hazard class(es)			
Not applicable	9	9	9
			
14.4. Packing group			
Not applicable	III	III	III
14.5. Environmental hazards			
Not applicable	Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes
No supplementary information available			

14.6. Special precautions for user

DOT

No data available

TDG

UN-No. (TDG) : UN3077

ULTRABOND® 1300 PART A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TDG Special Provisions

- : 16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the hazard or hazards posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A) of Part 3 (Documentation). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4 (Dangerous Goods Safety Marks).
- (2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name:
- (a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S.;
 - (b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S.;
 - (c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S.;
 - (d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S.;
 - (e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S.
- (3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment:
- (a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or
 - (b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS.
- 99 - (1) Mixtures of solids that are not dangerous goods and liquids or solids that are UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. or UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. may be handled, offered for transport or transported as UN3077 if there is no visible liquid when the dangerous goods are loaded into a means containment and during transport.
- (2) These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no accidental release of the dangerous goods that could endanger public safety.

Explosive Limit and Limited Quantity Index Excepted quantities (TDG)

- : 5 kg
: E1

IMDG

Special provision (IMDG) Limited quantities (IMDG) Excepted quantities (IMDG) Packing instructions (IMDG) Packing provisions (IMDG) IBC packing instructions (IMDG) IBC special provisions (IMDG) Tank instructions (IMDG) Tank special provisions (IMDG) EmS-No. (Fire) EmS-No. (Spillage) Stowage category (IMDG) Stowage and handling (IMDG)

- : 274, 335, 966, 967, 969
: 5 kg
: E1
: LP02, P002
: PP12
: IBC08
: B3
: BK1, BK2, BK3, T1
: TP33
: F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
: S-F - SPILLAGE SCHEDULE Foxtrot - WATER-SOLUBLE MARINE POLLUTANTS
: A
: SW23

IATA

PCA Excepted quantities (IATA) PCA Limited quantities (IATA) PCA limited quantity max net quantity (IATA) PCA packing instructions (IATA) PCA max net quantity (IATA) CAO packing instructions (IATA)

- : E1
: Y956
: 30kgG
: 956
: 400kg
: 956

ULTRABOND® 1300 PART A**Safety Data Sheet**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

CAO max net quantity (IATA) : 400kg
 Special provision (IATA) : A97, A158, A179, A197, A215
 ERG code (IATA) : 9L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information**15.1. US Federal regulations**

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations**CANADA****Oxirane, 2-[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)**

Listed on the Canadian DSL (Domestic Substances List)

Titanium oxide (TiO₂) (13463-67-7)

Listed on the Canadian DSL (Domestic Substances List)

Bisphenol A diglycidyl ether resin (1675-54-3)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations**Titanium oxide (TiO₂) (13463-67-7)**

Listed on IARC (International Agency for Research on Cancer)
 Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
Titanium oxide (TiO ₂)(13463-67-7)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 3/13/2024

ULTRABOND® 1300 PART A**Safety Data Sheet**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H351	Suspected of causing cancer
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.



ULTRABOND® 1300 PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 2/21/2024 Revision date: 3/13/2024 Supersedes: 3/12/2024 Version: 5.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : ULTRABOND® 1300 PART B

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Adhesives Technology Corporation
450 East Copans Road
Pompano Beach, Florida 33064
USA
T (800) 892-1880 - F (800) 362-3320
www.atcepoxy.com

1.4. Emergency telephone number

Emergency number : 800-255-3924
Operating hours 24 hours / 24 hours, 7 days a week

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 1	H318	Causes serious eye damage
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Reproductive toxicity Category 2	H361	Suspected of damaging fertility or the unborn child
Hazardous to the aquatic environment – Acute Hazard Category 1	H400	Very toxic to aquatic life
Hazardous to the aquatic environment – Chronic Hazard Category 1	H410	Very toxic to aquatic life with long lasting effects

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US)

: H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H361 - Suspected of damaging fertility or the unborn child
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects
Precautionary statements (GHS US) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 - Wash hands, forearms and face thoroughly after handling.

ULTRABOND® 1300 PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P272 - Contaminated work clothing must not be allowed out of the workplace.
 P273 - Avoid release to the environment.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P302+P352 - If on skin: Wash with plenty of water.
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 - If exposed or concerned: Get medical advice/attention.
 P310 - Immediately call a poison center or doctor.
 P321 - Specific treatment (see supplemental first aid instruction on this label).
 P332+P313 - If skin irritation occurs: Get medical advice/attention.
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
 P362+P364 - Take off contaminated clothing and wash it before reuse.
 P363 - Wash contaminated clothing before reuse.
 P391 - Collect spillage.
 P405 - Store locked up.
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Phenol, 4-nonyl-, branched	CAS-No.: 84852-15-3	≥ 10	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Repr. 2, H361 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Cyclic Ethyleneamine	CAS-No.: 140-31-8	5 – 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412
2,4,6-tris(dimethylaminomethyl)phenol	CAS-No.: 90-72-2	≥ 1	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319

ULTRABOND® 1300 PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
2-methylpentane-1,5-diamine	CAS-No.: 15520-10-2	≥ 1	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 3, H402

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.
----------------------	---

ULTRABOND® 1300 PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment

: Collect spillage.

Methods for cleaning up

: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information

: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

Hygiene measures

: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ULTRABOND® 1300 PART B

No additional information available

Cyclic Ethyleneamine (140-31-8)

No additional information available

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)

No additional information available

2-methylpentane-1,5-diamine (15520-10-2)

No additional information available

Phenol, 4-nonyl-, branched (84852-15-3)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls

: Ensure good ventilation of the work station.

Environmental exposure controls

: Avoid release to the environment.

ULTRABOND® 1300 PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Mixture contains one or more component(s) which have the following colour(s): Colourless to light yellow Light yellow Colourless White Colourless to white
Odor	: There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour: Irritating/pungent odour Smell of fish Amine-like odour Amine-like Odourless Mild odour Phenol odour
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

3/13/2024 (Revision date)

US - en

5/15

ULTRABOND® 1300 PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Cyclic Ethyleneamine (140-31-8)

LD50 oral rat	2097 mg/kg body weight (Rat, Male, Experimental value, Oral, 14 day(s))
LD50 oral	1470 mg/kg
LD50 dermal rabbit	866 mg/kg bw/day (24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))
LD50 dermal	880 mg/kg
ATE US (oral)	1470 mg/kg body weight
ATE US (dermal)	866 mg/kg body weight

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)

LD50 oral rat	2169 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 oral	1000 mg/kg
LD50 dermal rat	1280 mg/kg
LD50 dermal	1280 mg/kg
ATE US (oral)	1000 mg/kg body weight
ATE US (dermal)	1280 mg/kg body weight

2-methylpentane-1,5-diamine (15520-10-2)

LD50 oral rat	1690 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))
---------------	--

ULTRABOND® 1300 PART B**Safety Data Sheet**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-methylpentane-1,5-diamine (15520-10-2)	
LD50 dermal rat	1870 mg/kg body weight (Equivalent or similar to OECD 402, Rat, Male / female, Read-across, Dermal, 14 day(s))
LC50 Inhalation - Rat	4.9 mg/l air (Equivalent or similar to OECD 403, 1 h, Rat, Male / female, Experimental value, Inhalation (mist), 14 day(s))
ATE US (oral)	1690 mg/kg body weight
ATE US (dermal)	1870 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	4.9 mg/l/4h
ATE US (dust, mist)	4.9 mg/l/4h
Phenol, 4-nonyl-, branched (84852-15-3)	
LD50 oral rat	1412 mg/kg body weight (Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 oral	580 mg/kg
LD50 dermal rabbit	3160 mg/kg Source: ChemIDPlus
LD50 dermal	2037 mg/kg
ATE US (oral)	580 mg/kg body weight
ATE US (dermal)	2037 mg/kg body weight
Skin corrosion/irritation	: Causes skin irritation.
Cyclic Ethyleneamine (140-31-8)	
pH	11.5
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
pH	11 (10 %)
2-methylpentane-1,5-diamine (15520-10-2)	
pH	No data available in the literature
Phenol, 4-nonyl-, branched (84852-15-3)	
pH	No data available in the literature
Serious eye damage/irritation	: Causes serious eye damage.
Cyclic Ethyleneamine (140-31-8)	
pH	11.5
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
pH	11 (10 %)
2-methylpentane-1,5-diamine (15520-10-2)	
pH	No data available in the literature
Phenol, 4-nonyl-, branched (84852-15-3)	
pH	No data available in the literature
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.

3/13/2024 (Revision date)

US - en

7/15

ULTRABOND® 1300 PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Phenol, 4-nonyl-, branched (84852-15-3)	
NOAEL (animal/female, F0/P)	15 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 416 (Two-Generation Reproduction Toxicity Study), Remarks on results: other:Generation: All generations tested: F0, F1, F2, F3 (migrated information)
NOAEL (animal/male, F1)	15 mg/kg body weight Animal: rat, Animal sex: male, Guideline: other:EPA OPPTS 837.3800 (US EPA OPPTS 1998)
STOT-single exposure	: Not classified
2-methylpentane-1,5-diamine (15520-10-2)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Phenol, 4-nonyl-, branched (84852-15-3)	
LOAEL (oral,rat,90 days)	400 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
NOAEL (oral,rat,90 days)	100 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Cyclic Ethyleneamine (140-31-8)	
Viscosity, kinematic	No data available in the literature
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Viscosity, kinematic	206.186 mm²/s
2-methylpentane-1,5-diamine (15520-10-2)	
Viscosity, kinematic	No data available in the literature
Phenol, 4-nonyl-, branched (84852-15-3)	
Viscosity, kinematic	No data available in the literature
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Very toxic to aquatic life with long lasting effects.

Cyclic Ethyleneamine (140-31-8)	
LC50 - Fish [1]	2190 mg/l (96 h, Pimephales promelas, Static system, Fresh water, Experimental value)
EC50 - Crustacea [1]	58 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Experimental value, GLP)
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	> 1000 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Fresh water, Experimental value, GLP)

ULTRABOND® 1300 PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
LC50 - Fish [1]	175 mg/l (APHA, 96 h, Cyprinus carpio, Static system, Fresh water, Experimental value, Nominal concentration)
LC50 - Fish [2]	180 – 240 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 72h - Algae [1]	84 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 96h - Algae [1]	34.812 mg/l Source: ECOSAR
ErC50 algae	84 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, GLP)
2-methylpentane-1,5-diamine (15520-10-2)	
LC50 - Fish [1]	1825 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Static system, Fresh water, Read-across, Nominal concentration)
EC50 - Crustacea [1]	19.8 – 23.4 mg/l (Equivalent or similar to OECD 202, 48 h, Daphnia magna, Static system, Fresh water, Read-across, Nominal concentration)
ErC50 algae	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Read-across, GLP)
Phenol, 4-nonyl-, branched (84852-15-3)	
LC50 - Fish [1]	0.08 mg/l (ASTM E729-96, 96 h, Hybopsis monacha, Static system, Fresh water, Experimental value)
EC50 - Crustacea [1]	0.084 mg/l (ASTM E729-88, 48 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, Lethal)
EC50 72h - Algae [1]	0.33 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	0.027 mg/l
NOEC chronic fish	0.006 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '91 d'
12.2. Persistence and degradability	
Cyclic Ethyleneamine (140-31-8)	
Not rapidly degradable	
Persistence and degradability	Not readily biodegradable in water.
Chemical oxygen demand (COD)	0.56 g O ₂ /g substance
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Not rapidly degradable	
Persistence and degradability	Not readily biodegradable in water.
2-methylpentane-1,5-diamine (15520-10-2)	
Persistence and degradability	Readily biodegradable in water.
Phenol, 4-nonyl-, branched (84852-15-3)	
Not rapidly degradable	
Persistence and degradability	Biodegradability in soil: no data available. Inherently biodegradable.

ULTRABOND® 1300 PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential

Cyclic Ethyleneamine (140-31-8)	
BCF - Fish [1]	0.3 – 6.3 (OECD 305: Bioconcentration: Flow-Through Fish Test, 6 week(s), Cyprinus carpio, Flow-through system, Fresh water, Read-across)
Partition coefficient n-octanol/water (Log Pow)	-1.48 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Partition coefficient n-octanol/water (Log Pow)	-0.66 (Experimental value, EPA OPPTS 830.7550: Partition Coefficient (n-octanol/water), Shake Flask Method, 21.5 °C)
Bioaccumulative potential	Not bioaccumulative.
2-methylpentane-1,5-diamine (15520-10-2)	
Partition coefficient n-octanol/water (Log Pow)	≤ 1 (Experimental value, US EPA, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Phenol, 4-nonyl-, branched (84852-15-3)	
BCF - Fish [1]	1200 – 1300 (Equivalent or similar to OECD 305, 16 day(s), Gasterosteus aculeatus, Flow-through system, Salt water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	5.4 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 23 °C)
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).

12.4. Mobility in soil

Cyclic Ethyleneamine (140-31-8)	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	4.57 (log Koc, Read-across, GLP)
Ecology - soil	Low potential for mobility in soil.
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.32 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.
2-methylpentane-1,5-diamine (15520-10-2)	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.159 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Low potential for adsorption in soil.
Phenol, 4-nonyl-, branched (84852-15-3)	
Surface tension	38.9 mN/m (20 °C, EU Method A.5: Surface tension)
Ecology - soil	Adsorbs into the soil.

ULTRABOND® 1300 PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.5. Other adverse effects

No additional information available


SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
3082	UN3082	3082	3082
14.2. Proper Shipping Name			
Environmentally hazardous substances, liquid, n.o.s. (Phenol, 4-nonyl-, branched ; Cyclic Ethyleneamine)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Phenol, 4-nonyl-, branched ; Cyclic Ethyleneamine)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Phenol, 4-nonyl-, branched ; Cyclic Ethyleneamine ; Phenol, 4-nonyl-, branched ; Cyclic Ethyleneamine)	Environmentally hazardous substance, liquid, n.o.s. (Phenol, 4-nonyl-, branched ; Cyclic Ethyleneamine ; Phenol, 4-nonyl-, branched ; Cyclic Ethyleneamine)
14.3. Transport hazard class(es)			
9	9	9	9
			
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes
No supplementary information available			

14.6. Special precautions for user

DOT

Transport regulations (DOT)

: As per 49 CFR 171.4(c)(1) packaging requirements do not apply to this product if shipped in non-bulk packaging and is not shipped via vessel for domestic travel.

UN-No.(DOT)

: UN3082

ULTRABOND® 1300 PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)

: 8 - A hazardous substance that is not a hazardous waste may be shipped under the shipping description "Other regulated substances, liquid or solid, n.o.s.", as appropriate. In addition, for solid materials, special provision B54 applies.

146 - This description may be used for a material that poses a hazard to the environment but does not meet the definition for a hazardous waste or a hazardous substance, as defined in 171.8 of this subchapter, or any hazard class as defined in Part 173 of this subchapter, if it is designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination.

173 - An appropriate generic entry may be used for this material.

335 - Mixtures of solids that are not subject to this subchapter and environmentally hazardous liquids or solids may be classified as "Environmentally hazardous substances, solid, n.o.s.," UN3077 and may be transported under this entry, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each transport unit must be leak-proof when used as bulk packaging.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx)

: 155

DOT Packaging Non Bulk (49 CFR 173.xxx)

: 49 CFR 171.4(c)(1)

DOT Packaging Bulk (49 CFR 173.xxx)

: 241

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)

: No Limit

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)

: No Limit

DOT Vessel Stowage Location

: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

TDG

UN-No. (TDG)

: UN3082

ULTRABOND® 1300 PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TDG Special Provisions

: 16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the hazard or hazards posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A) of Part 3 (Documentation). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4 (Dangerous Goods Safety Marks).
 (2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name:
 (a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S.;
 (b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S.;
 (c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S.;
 (d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S.; or
 (e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S.
 (3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment:
 (a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or
 (b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS.99 - (1) Mixtures of solids that are not dangerous goods and liquids or solids that are UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. or UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. may be handled, offered for transport or transported as UN3077 if there is no visible liquid when the dangerous goods are loaded into a means containment and during transport.
 (2) These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no accidental release of the dangerous goods that could endanger public safety.

Explosive Limit and Limited Quantity Index : 5 L
 Excepted quantities (TDG) : E1
 Emergency Response Guide (ERG) Number : 171

IMDG

Special provision (IMDG) : 274, 335, 969
 Limited quantities (IMDG) : 5 L
 Excepted quantities (IMDG) : E1
 Packing instructions (IMDG) : LP01, P001
 Packing provisions (IMDG) : PP1
 IBC packing instructions (IMDG) : IBC03
 Tank instructions (IMDG) : T4
 Tank special provisions (IMDG) : TP1, TP29
 EmS-No. (Fire) : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
 EmS-No. (Spillage) : S-F - SPILLAGE SCHEDULE Foxtrot - WATER-SOLUBLE MARINE POLLUTANTS
 Stowage category (IMDG) : A

IATA

PCA Excepted quantities (IATA) : E1
 PCA Limited quantities (IATA) : Y964
 PCA limited quantity max net quantity (IATA) : 30kgG
 PCA packing instructions (IATA) : 964
 PCA max net quantity (IATA) : 450L
 CAO packing instructions (IATA) : 964
 CAO max net quantity (IATA) : 450L

ULTRABOND® 1300 PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Special provision (IATA) : A97, A158, A197, A215
ERG code (IATA) : 9L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

2-methylpentane-1,5-diamine	CAS-No. 15520-10-2	≥ 1%
-----------------------------	--------------------	------

Contains chemical(s) subject to TSCA 12b export notification if product is shipped outside the U.S

Phenol, 4-nonyl-, branched	CAS-No. 84852-15-3	≥ 10%
----------------------------	--------------------	-------

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Phenol, 4-nonyl-, branched	CAS-No. 84852-15-3	≥ 10%
----------------------------	--------------------	-------

15.2. International regulations

CANADA

Cyclic Ethyleneamine (140-31-8)

Listed on the Canadian DSL (Domestic Substances List)

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)

Listed on the Canadian DSL (Domestic Substances List)

Phenol, 4-nonyl-, branched (84852-15-3)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Cyclic Ethyleneamine (140-31-8)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Phenol, 4-nonyl-, branched (84852-15-3)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

ULTRABOND® 1300 PART B**Safety Data Sheet**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
Cyclic Ethyleneamine(140-31-8)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 3/13/2024

Full text of H-phrases	
H227	Combustible liquid
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H361	Suspected of damaging fertility or the unborn child
H400	Very toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.