

QUIKRETE**CEMENT & CONCRETE PRODUCTS™**

Distributed By:

UNITIS
CONTRACTOR SUPPLIESSan Diego: 1-858-332-2133
El Cajon: 1-619-270-7100
Buena Park: 1-714-522-0055
Corona: 1-951-231-9700
www.unitisonline.com

B3: Packaged Aggregates

SAFETY DATA SHEET
(Complies with OSHA 29 CFR 1910.1200)

SECTION I: PRODUCT IDENTIFICATION

The QUIKRETE® Companies
One Securities Centre
3490 Piedmont Road, Suite 1300
Atlanta, GA 30305Emergency Telephone Number
(770) 216-9580
Information Telephone Number
(770) 216-9580SDS B3
Revision: May-15

QUIKRETE® Product Name	Code #
Agricultural Limestone	1111-50
White Marking Lime	1111-60
Pelletized Lime	1125-40
Crushed Stone Dust – 25 Kg	1151-62
White Marble Rock	1175-02
Mini Marble	1275-00
Athletic Field Marker	1954-00
Monarch Mountain DCF	1954-05
White Marble Mix	1954-06
Monarch Mountain Landscape Marble	2500/3500
Monarch Mountain Aqua White Pool Coat	9903
Monarch Mountain Pulverized Limestone	9904
Deco Pebbles	9905
Marble Chips	9906

Product Use: Limestone aggregates for use in construction and landscaping

SECTION II - HAZARD IDENTIFICATION

Hazard-determining components of labeling: Silica**2.1 Classification of the substance or mixture**

Carcinogen – Category 1A

Specific Target Organ Toxicity Single Exposure – Category 3

Specific Target Organ Toxicity Repeat Exposure – Category 1

Eye Irritant – Category 2B

2.2a Signal word DANGER!

QUIKRETE**CEMENT & CONCRETE PRODUCTS™**

2.2b Hazard Statements

May cause cancer through chronic inhalation

May cause respiratory irritation

Causes damage to lungs through prolonged or repeated inhalation

Causes eye irritation if particles or dust get in eye

Industrial hygiene experts have studied long-term daily use of silica sands in sand-blasting and other occupations generating extreme volumes of dust. They have determined that long term, daily exposure to high concentrations of blasting sand dust causes damage to the lungs, may cause silicosis, and may cause cancer. **Do not use for sand blasting.** There are extensive OSHA precautions required for sand blasting.

2.2c Pictograms



2.2d Precautionary statements

Do not handle until all safety precautions have been read and understood.

Wear protective gloves, eye protection, and protective clothing.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Use only in a well-ventilated area.

Do not breathe dust.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately seek medical advice or attention if symptoms are significant or persist.

Dispose of contents/containers in accordance with all regulations.

2.3 Additional Information

2.3a HNO3 – Hazards not otherwise classified: Not applicable

2.3b Unknown Acute Toxicity: None

2.3c WHMIS Classification

QUIKRETE**CEMENT & CONCRETE PRODUCTS™**

Class D2A – Chronic Toxic Effects – Carcinogen
 Class D2B – Eye Irritant

2.3d Label Elements According To WHMIS**Hazard Symbols****Signal Word**

DANGER!

SECTION III - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components	CAS No.	% by Weight
Crushed Limestone	01317-65-3	90-99
Sand, Silica, Quartz	14808-60-7	1-10

The concentrations ranges are provided due to batch-to-batch variability.

SECTION IV – FIRST AID MEASURES**4.1 Description of the first-aid measures****General information:**

After inhalation: Remove person to fresh air. If breathing is difficult, administer oxygen. If not breathing, give artificial respiration. In case of unconsciousness, place patient stably in side position for transportation.

After skin contact: Wash skin with cool water and pH-neutral soap or a mild detergent. If significant skin irritation or rash occurs: get medical advice or attention.

After eye contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

After swallowing: Do not induce vomiting. If conscious, have the victim drink plenty of water and call a physician immediately. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms/effects, acute and delayed

**CEMENT & CONCRETE PRODUCTS™**

Inhalation: May cause respiratory tract irritation. Causes damage to organs through prolonged or repeated inhalation. This product contains crystalline silica. Prolonged or repeated inhalation of respirable silica from this product can cause silicosis.

Skin contact: Causes mechanical skin irritation.

Eye Contact: Causes eye irritation if particles or dust get in eye.

Ingestion: Ingestion of large quantities may cause discomfort and/or distress, nausea or vomiting.

4.3 Indication of immediate medical attention and special treatment needed:

Immediately seek medical advice or attention if symptoms are significant or persist.

SECTION V - FIRE FIGHTING MEASURES

5.1 Flammability of the Product: Non-flammable and non-combustible

5.2 Suitable extinguishing agents: Treat for surrounding material

5.3 Special hazards arising from the substance or mixture: None

5.3a Products of Combustion: None

5.3b Explosion Hazards in Presence of Various Substances: Non-explosive in presence of shocks

SECTION VI – ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures: Wear personal protective equipment (See section VIII). Keep unprotected persons away.

6.2 Methods and material for containment and cleaning up:

Do not allow to enter sewers/ surface or ground water. Dispose of unwanted materials and containers properly in accordance with all regulations.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND STORAGE

7.1 Handling

Precautions for safe handling: Do not use for sand blasting. There are extensive OSHA precautions required for sand blasting. Ensure good ventilation/exhaustion at the workplace. DO NOT BREATHE DUST. In dusty environments, the use of an OSHA, MSHA or NIOSH approved respirator and tight fitting goggles is recommended. Wear appropriate PPE (See section 8). Do not mix with other chemical products, except as indicated by the manufacturer. Do not get in eyes, on skin or clothing. Good housekeeping is important to prevent accumulation of dust.

7.2 Storage



CEMENT & CONCRETE PRODUCTS™

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep out of the reach of children.

SECTION VIII – EXPOSURE CONTROL MEASURES / PERSONAL PROTECTION

8.1 Components with limit values that require monitoring at the workplace:

Hazardous Components	CAS No.	PEL (OSHA) mg/M ³	TLV (ACGIH) mg/M ³
Silica Sand, crystalline	14808-60-7	0.1	0.025 (resp)
Limestone Dust	01317-65-3	5 (resp) 15 (total)	10 (resp)

8.2 Exposure Controls

Use ventilation adequate to keep exposures below recommended exposure limits.

8.3 General protective and hygienic measures

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

8.3a Personal protective equipment

Protection of hands:

Wear gloves of adequate length to offer appropriate skin protection from incidental contact. General duty work gloves have been found to offer adequate protection for most intended uses.

Eye protection:

Wear approved eye protection properly fitted dust- proof chemical safety glasses.

Respiratory protection:

A NIOSH-approved dust mask or filtering face piece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional, following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS

General Information

Appearance	Form: Granular Solid Color: Varies Odor: None
pH-value at 20°C (68 °F):	Not applicable
Boiling point/Boiling range:	Not applicable
Flash point:	Not applicable



CEMENT & CONCRETE PRODUCTS™

Auto igniting: Product is not self-igniting
Vapor pressure at 21°C (70°F) Not applicable
Density at 25°C (77 °F): 2.5-2.8
Solubility in / Miscibility with
Water: Insoluble
VOC content: 0 g/L VOC

SECTION X – STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal storage conditions. Keep in dry storage.

10.3 Possibility of hazardous reaction

No dangerous reaction known under conditions of normal use.

10.4 Thermal decomposition / conditions to be avoided

No decomposition if used according to specifications.

10.5 Incompatible materials

Contact of silica with powerful oxidizing agents such as fluorine, chlorine trifluoride, manganese trioxide, or oxygen difluoride may cause fires

10.6 Hazardous Decomposition or By-products

Silica will dissolve in Hydrofluoric Acid and produce a corrosive gas – silicon tetrafluoride.

SECTION XI – TOXICOLOGICAL INFORMATION

11.1 Exposure Routes: Inhalation, skin contact, eye contact, or ingestion.

11.2 Symptoms related to physical/chemical/toxicological characteristics:

Inhalation: May cause respiratory tract irritation. Causes damage to organs through prolonged or repeated exposure. This product contains crystalline silica. Prolonged or repeated inhalation of respirable silica from this product can cause silicosis.

Skin contact: May cause mechanical skin irritation.

Eye Contact: Causes eye irritation if particles or dust gets in eye.

Ingestion: Ingestion of large quantities may cause discomfort and/or distress.

11.3 Delayed, immediate and chronic effects of short-term and long-term exposure

Short Term

Skin Corrosion/Irritation: Not applicable

Serious Eye Damage/Irritation: Causes eye irritation if particles or dust gets in eye

**CEMENT & CONCRETE PRODUCTS™**

Respiratory Sensitization: Not applicable

Skin Sensitization: Not applicable

Specific Target Organ Toxicity-Single Exposure: (Category 3) May cause respiratory irritation

Aspiration Hazard: Not applicable

Long Term

Carcinogenicity: May cause cancer through chronic inhalation.

Germ Cell Mutagenicity: Not applicable

Reproductive Toxicity: Not applicable

Specific Target Organ Toxicity- Repeated Exposure: (Category 1) Causes damage to lungs through prolonged/repeated exposure

Synergistic/Antagonistic Effects: Not applicable

SECTION XII – ECOLOGICAL INFORMATION

12.1 Ecotoxicity

No further relevant information available.

12.2 Persistence and degradability

No further relevant information available.

12.3 Bioaccumulative potential:

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

12.5 Other Adverse Effects

No further relevant information available.

SECTION XIII – DISPOSAL CONSIDERATIONS

13.1 Waste Disposal Method

The packaging and material may be land filled; however, material should be covered to minimize generation of airborne dust. This product is not classified as a hazardous waste under the authority of the RCRA (40CFR 261) or CERCLA (40CFR 117&302). Disposal must be made in accordance with local, state and federal regulations.

13.2 Other disposal considerations**Uncleaned packaging**

Recommendation: Disposal must be made in accordance with local, state and federal regulations.

Recommended cleansing agent: Water, if necessary with cleansing agents.

SECTION XIV – TRANSPORT INFORMATION



CEMENT & CONCRETE PRODUCTS™

	DOT (U.S.)	TDG (Canada)
UN-Number	Not Regulated	Not Regulated
UN proper shipping name	Not Regulated	Not Regulated
Transport Hazard Class(es)	Not Regulated	Not Regulated
Packing Group (if applicable)	Not Regulated	Not Regulated

14.1 Environmental hazards:

Not applicable

14.2 Transport in bulk according to Annex II of Marpol 73/78 and the IBC Code

Not applicable

14.3 Special precautions for user

Do not handle until all safety precautions have been read and understood.

SECTION XV – OTHER REGULATORY INFORMATION

15.1 Safety, Health and Environmental Regulations/Legislations specific for the chemical

Canada

WHMIS Classification: Considered to be a D2A and D2B hazardous material under the Hazardous Products Act as defined by the Controlled Products Regulations and subject to the requirements of Health Canada's Workplace Hazardous Material Information (WHMIS). This document complies with the WHMIS requirements of the Hazardous Products Act (HPA) and the CPR.

15.2 US Federal Information

SARA 302/311/312/313 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302, 311, 312 or 313.

RCRA: Crystalline silica (quartz) is not classified as a hazardous waste under the Resource Conservation and Recovery Act, or its regulations, 40 CFR §261 et seq.

CERCLA: Crystalline silica (quartz) is not classified as a hazardous substance under regulations of the Comprehensive Environmental Response Compensation and Liability Act (CERCLA), 40 CFR §302.

Emergency Planning and Community Right to Know Act (SARA Title III): Crystalline silica (quartz) is not an extremely hazardous substance under Section 302 and is not a toxic chemical subject to the requirements of Section 313.

FDA: Silica is included in the list of substances that may be included in coatings used in food contact surfaces, 21 CFR §175.300(b)(3)(xxvi).

CEMENT & CONCRETE PRODUCTS™

NTP: Respirable crystalline silica, primarily quartz dusts occurring in industrial and occupational settings, is classified as Known to be a Human Carcinogen.

OSHA Carcinogen: Crystalline silica (quartz) is not listed.

15.3 State Right to Know Laws

California Prop. 65 Components

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

California Inhalation Reference Exposure Level (REL): California established a chronic REL of 3 µg for silica (crystalline, respirable). A chronic REL is an airborne level of a substance at or below which no adverse health effects are anticipated in individuals indefinitely exposed to the substance at that level.



Massachusetts Toxic Use Reduction Act: Silica, crystalline (respirable size, <10 microns) is “toxic” for purposes of the Massachusetts Toxic Use Reduction Act.

15.4 Global Inventories

DSL All components of this product are on the Canadian DSL list.

TSCA No.: Crystalline silica (quartz) appears on the EPA TSCA inventory under the CAS No. 14808-60-7. All constituents are listed in the TSCA inventory.

15.5 NFPA Ratings



QUIKRETE[®]**CEMENT & CONCRETE PRODUCTS™**

SECTION XVI – OTHER INFORMATION

Last Updated: May 26, 2015

NOTE: The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to silica contained in our products.

Prepared by

The QUIKRETE[®] Companies
Phone (800) 282-5828
www.QUIKRETE.com

End of SDS

Distributed By:

UNITIS
CONTRACTOR SUPPLIES

San Diego: 1-858-332-2133
El Cajon: 1-619-270-7100
Buena Park: 1-714-522-0055
Corona: 1-951-231-9700
www.unitisonline.com