

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 03/29/2017 Revision date: 01/31/2018 Version: 1.0



SECTION 1: Identification

Product identifier

: Mixtures Product form

Product name : Sakrete Fast Setting Concrete Mix

Product code : 65305535 - 50lb bag

Recommended use and restrictions on use

Recommended use : Various

Supplier 1.3.

Manufacturer

Sakrete Of North America 625 Griffith Rd., Ste 100 Charlotte, NC 28217- USA T 866-725-7383

Distributor

Add the name, address and tel. number of the Canadian manufacturer

or importer who operates in Canada

Emergency telephone number

Emergency number : For Hazardous Materials [or Dangerous Goods] Incident

Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night

1-800-424-9300 [USA] / +1 703-527-3887 [CAN]

SECTION 2: Hazard identification

Classification of the substance or mixture

Classification (GHS-CA)

Skin Irrit. 2 H315 Eye Dam. 1 H318 Carc. 1A H350 STOT RE 1 H372

GHS Label elements, including precautionary statements

GHS-CA labelling

Hazard pictograms (GHS-CA)



GHS08

Signal word (GHS-CA) : Danger

Hazard statements (GHS-CA) : H315 - Causes skin irritation

H318 - Causes serious eye damage

H350 - May cause cancer

H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-CA) P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe dust

P264 - Wash hands, forearms and face thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P280 - Wear eye protection, face protection, protective gloves, protective clothing

P308+P313 - IF exposed or concerned: Get medical advice/attention

P302+P352 - IF ON SKIN: Wash with plenty of water

P362+P364 - Take off contaminated clothing and wash it before reuse P332+P313 - If skin irritation occurs: Get medical advice/attention

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing P310 - Immediately call a POISON CENTER or doctor

P405 - Store locked up

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation

Other hazards

Other hazards not contributing to the

classification

: Not applicable.

01/31/2018 EN (English) Page 1

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Unknown acute toxicity (GHS-CA)

Not applicable

SECTION 3: Composition/information on ingredients

Substances

Not applicable

3.2 **Mixtures**

Name	Product identifier	%
Quartz	(CAS-No.) 14808-60-7	83.67
Cement, portland, chemicals	(CAS-No.) 65997-15-1	10.58
Limestone	(CAS-No.) 1317-65-3	0.56

SECTION 4: First-aid measures

Description of first aid measures

First-aid measures after inhalation

: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact

In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

First-aid measures after eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.

If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Immediately call a POISON CENTER or

First-aid measures after ingestion

doctor/physician.

Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation

: May cause respiratory irritation.

Symptoms/effects after skin contact

Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.

Symptoms/effects after eye contact

Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Symptoms/effects after ingestion

: Harmful if swallowed. May cause stomach distress, nausea or vomiting.

Immediate medical attention and special treatment, if necessary

Other medical advice or treatment

: Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Fire-fighting measures

Suitable extinguishing media

Suitable extinguishing media : Treat for surrounding material.

Unsuitable extinguishing media

Unsuitable extinguishing media : Not available.

5.3. Specific hazards arising from the hazardous product

Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon.

Special protective equipment and precautions for fire-fighters

Firefighting instructions : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to General measures unnecessary and unprotected personnel.

Methods and materials for containment and cleaning up

For containment : Contain spill, then place in a suitable container. Do not flush to sewer or allow to enter

waterways. Use appropriate Personal Protective Equipment (PPE). Minimize generation of

Methods for cleaning up : Vacuum or sweep material and place in a disposal container.

01/31/2018 EN (English) 2/5

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

Precautions for safe handling

Precautions for safe handling

Do not swallow. Avoid contact with skin and eyes. Good housekeeping is important to prevent accumulation of dust. Avoid generating and breathing dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Handle and open container with care. When using do not eat, drink or smoke.

: Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking. Hygiene measures

Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep out of the reach of children. Store in dust-tight, dry, labelled containers. Keep container tightly closed when not in use. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area. Do not store in an area equipped with emergency water sprinklers.

SECTION 8: Exposure controls/personal protection

Control parameters

Cement, portland, chemicals (65997-15-1)			
USA - ACGIH	ACGIH TWA (mg/m³)	1 mg/m³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)	
Quartz (14808-60-7)			
USA - ACGIH	ACGIH TWA (mg/m³)	0.025 mg/m³ (respirable particulate matter)	

Appropriate engineering controls

Appropriate engineering controls

: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits

Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable waterproof gloves

Eye protection:

Wear approved eye protection (properly fitted dust- or splash-proof chemical safety goggles) and face protection (face shield).

Skin and body protection:

Wear suitable waterproof protective clothing

Respiratory protection:

A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

Other information:

Handle according to established industrial hygiene and safety practices. Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state : Solid Powder Appearance Colour Various Odour Characteristic Odour threshold : No data available : 12 - 13

Hq

Relative evaporation rate (butylacetate=1) : No data available Relative evaporation rate (ether=1) : No data available Melting point : No data available Freezing point : No data available Boiling point : No data available

01/31/2018 EN (English) 3/5

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

No data available Flash point Auto-ignition temperature : No data available Decomposition temperature : No data available Flammability (solid, gas) Not flammable Vapour pressure No data available Vapour pressure at 50 °C : No data available Relative density : No data available Solubility No data available Partition coefficient n-octanol/water No data available : No data available Viscosity, kinematic **Explosive limits** : No data available

9.2. Other information

VOC content : 0%, Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal storage conditions. Keep dry in storage.

Possibility of hazardous reactions : No dangerous reaction known under conditions of normal use.

Conditions to avoid : Incompatible materials. Moisture.

Incompatible materials : Wet cement is alkaline and incompatible with acid, ammonium salts and aluminum metal.

Hazardous decomposition products : May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.

Acute toxicity (dermal) : Not classified.

Acute toxicity (inhalation) : Not classified.

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified.
Germ cell mutagenicity : Not classified.
Carcinogenicity : May cause cancer.
Reproductive toxicity : Not classified.
STOT-single exposure : Not classified.

STOT-repeated exposure : Causes damage to lungs through prolonged or repeated exposure. Respirable crystalline silica

in the form of quartz or cristobalite from occupational sources is listed by the International Agency for Research on Cancer (IARC) and National Toxicology Program (NTP) as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of dust exposure and the length of

time (usually years) of exposure.

Aspiration hazard : Not classified.

Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in

permanent injury. Do not live the live that the discrete built possibly resulting in

prolonged contact with skin. Handling can cause dry skin.

Symptoms/effects after eye contact : Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may

include discomfort or pain, excess blinking and tear production, with possible redness and

swelling.

Symptoms/effects after ingestion : Harmful if swallowed. May cause stomach distress, nausea or vomiting.

01/31/2018 EN (English) 4/5

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No ecological consideration when used according to directions. Normal dilution of this product

to drains, sewers, septic systems and treatment plants is not considered environmentally

harmful.

12.2. Persistence and degradability

Sakrete Fast Setting Concrete Mix

Persistence and degradability No data available.

12.3. Bioaccumulative potential

Sakrete Fast Setting Concrete Mix

Bioaccumulative potential No data available.

12.4. Mobility in soil

Sakrete Fast Setting Concrete Mix

Ecology - soil No data available.

12.5. Other adverse effects

Other adverse effects : No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal

regulations.

SECTION 14: Transport information

14.1. Basic shipping description

In accordance with TDG

Transportation of Dangerous Goods

Not regulated for transport

14.2. Transport information/DOT

No additional information available

14.3. Air and sea transport

No additional information available

SECTION 15: Regulatory information

15.1. National regulations

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

SECTION 16: Other information

Date of issue : 03/29/2017

Revision date : 03/29/2017

Prepared by : Nexreg Compliance Inc.

www.Nexreg.com



Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Distributed By:

UNITS

CONTRACTOR SUPPLIES

San Diego: 1-858-332-2133

El Cajon: 1-819-270-7100

Buena Park: 1-714-522-0055

Corona: 1-951-231-9700

www.unitisonline.com

01/31/2018 EN (English) 5/5