

Lockstop Primer Adhesive

Revision Date 09/29/2016

Distributed By:



San Diego: 1-858-332-2133
 El Cajon: 1-619-270-7100
 Buena Park: 1-714-522-0055
 Corona: 1-951-231-9700
 www.unitisonline.com



Print Date 09/29/2016

1. Identification

Product name : Lockstop Primer Adhesive

Supplier : Sika Corporation
 201 Polito Avenue
 Lyndhurst, NJ 07071
 USA
 www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300
 INTERNATIONAL: 703-527-3887

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

2. Hazards identification

GHS Classification

| | |
|---|---|
| Flammable liquids, Category 3 | H226: Flammable liquid and vapor. |
| Skin irritation, Category 2 | H315: Causes skin irritation. |
| Eye irritation, Category 2A | H319: Causes serious eye irritation. |
| Carcinogenicity, Category 2 (Inhalation) | H351: Suspected of causing cancer if inhaled. |
| Specific target organ systemic toxicity - single exposure, Category 3, Respiratory system | H335: May cause respiratory irritation. |
| , Central nervous system | |
| Specific target organ systemic toxicity - repeated exposure, Category 2 (Inhalation) | H336: May cause drowsiness or dizziness. |
| Specific target organ systemic toxicity - repeated exposure, Category 2 (Dermal) | H373: May cause damage to organs through prolonged or repeated exposure if inhaled. |
| Aspiration hazard, Category 1 | H373: May cause damage to organs through prolonged or repeated exposure in contact with skin. |
| | H304: May be fatal if swallowed and enters airways. |

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Lockstop Primer Adhesive



Revision Date 09/29/2016

Print Date 09/29/2016

- Hazard Statements** : H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer if inhaled.
H373 May cause damage to organs through prolonged or repeated exposure in contact with skin.
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.
- Precautionary Statements** : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face protection.
P281 Use personal protective equipment as required.
Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
Disposal:
P501 Dispose of contents/ container to an approved waste



disposal plant.

Warning : Reports have associated repeated and prolonged exposure to some of the chemicals in this product with permanent brain, liver, kidney and nervous system damage. Intentional misuse by deliberate concentration and inhalation of vapors may be harmful or fatal.

See Section 11 for more detailed information on health effects and symptoms.

There are no hazards not otherwise classified that have been identified during the classification process.

There are no ingredients with unknown acute toxicity used in a mixture at a concentration $\geq 1\%$.

3. Composition/information on ingredients

Hazardous ingredients

| Chemical name | CAS-No. | Concentration (%) |
|---------------|-----------|-------------------|
| Asphalt | 8052-42-4 | > 40 - < 50 % |
| xylene | 1330-20-7 | > 1 - < 10 % |
| ethylbenzene | 100-41-4 | > 1 - < 5 % |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

If inhaled : Move to fresh air.
Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not induce vomiting without medical advice.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Take victim immediately to hospital.

Most important symptoms and effects, both acute and delayed : Risk of serious damage to the lungs (by aspiration).
irritant effects

Aspiration may cause pulmonary edema and pneumonitis.
Cough
Respiratory disorder



Excessive lachrymation
 Erythema
 Dermatitis
 Loss of balance
 Vertigo
 See Section 11 for more detailed information on health effects and symptoms.

May be fatal if swallowed and enters airways.
 Causes skin irritation.
 Causes serious eye irritation.
 May cause respiratory irritation.
 May cause drowsiness or dizziness.
 Suspected of causing cancer if inhaled.
 May cause damage to organs through prolonged or repeated exposure in contact with skin.
 May cause damage to organs through prolonged or repeated exposure if inhaled.

Protection of first-aiders : Move out of dangerous area.
 Consult a physician.
 Show this material safety data sheet to the doctor in attendance.

Notes to physician : Treat symptomatically.

5. Fire-fighting measures

Suitable extinguishing media : Alcohol-resistant foam
 Carbon dioxide (CO₂)
 Dry chemical

Unsuitable extinguishing media : Water
 High volume water jet

Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.

Specific extinguishing methods : Use water spray to cool unopened containers.
 Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
 Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
 Remove all sources of ignition.
 Deny access to unprotected persons.
 Beware of vapors accumulating to form explosive



- concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

7. Handling and storage

- Advice on safe handling : Do not breathe vapors or spray mist.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Open drum carefully as content may be under pressure.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).
Follow standard hygiene measures when handling chemical products.
- Conditions for safe storage : Store in original container.
Keep in a well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Store in accordance with local regulations.
- Materials to avoid : No data available

8. Exposure controls/personal protection

| Component | CAS-No. | Basis ** | Value | Exposure limit(s)* / Form of exposure |
|-----------|-----------|----------|-------|---|
| Asphalt | 8052-42-4 | ACGIH | TWA | 0.5 mg/m ³ Inhalable fraction |
| | | ACGIH | TWA | 0.5 mg/m ³ Fume, inhalable fraction |
| xylene | 1330-20-7 | OSHA Z-1 | TWA | 100 ppm 435 mg/m ³ |
| | | OSHA P0 | STEL | 150 ppm 655 mg/m ³ |

Lockstop Primer Adhesive



Revision Date 09/29/2016

Print Date 09/29/2016

| | | | | |
|--------------|----------|----------|------|----------------------|
| | | OSHA P0 | TWA | 100 ppm 435 mg/m3 |
| | | ACGIH | TWA | 100 ppm |
| | | ACGIH | STEL | 150 ppm |
| | | CAL PEL | STEL | 150 ppm 655 mg/m3 |
| | | CAL PEL | C | 300 ppm |
| | | CAL PEL | PEL | 100 ppm 435 mg/m3 |
| ethylbenzene | 100-41-4 | ACGIH | TWA | 20 ppm |
| | | ACGIH | STEL | 125 ppm |
| | | OSHA Z-1 | TWA | 100 ppm 435 mg/m3 |
| | | OSHA P0 | TWA | 100 ppm 435 mg/m3 |
| | | OSHA P0 | STEL | 125 ppm 545 mg/m3 |
| | | CAL PEL | PEL | 5 ppm 22 mg/m3 |
| | | CAL PEL | STEL | 30 ppm 130 mg/m3 |

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

****Basis**

ACGIH. Threshold Limit Values (TLV)

OSHA P0. Table Z-1, Limit for Air Contaminat (1989 Vacated Values)

OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant

OSHA P2. Permissible Exposure Limits (PEL), Table Z-2

OSHA Z3. Table Z-3, Mineral Dust

Engineering measures

: Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other



engineering controls to keep worker exposure below any recommended or statutory limits.
The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

Personal protective equipment

- Respiratory protection** : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
- The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection**
Remarks : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection** : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures** : Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product.
Remove respiratory and skin/eye protection only after vapors have been cleared from the area.
Remove contaminated clothing and protective equipment before entering eating areas.
Wash thoroughly after handling.

9. Physical and chemical properties

- Appearance** : viscous liquid
- Color** : dark brown
black
- Odor** : aromatic
hydrocarbon-like
- Odor Threshold** : No data available
- Flash point** : 80.4 - 89.4 °F (26.9 - 31.9 °C)
- Ignition temperature** : 865.9 - 984.0 °F (463.3 - 528.9 °C)



| | |
|---|---|
| | 869 °F (465 °C) |
| Decomposition temperature | : No data available |
| Lower explosion limit (Vol%) | : 1 %(V) |
| Upper explosion limit (Vol%) | : 7 %(V) |
| Flammability (solid, gas) | : No data available |
| Oxidizing properties | : No data available |
| pH | : Note: Not applicable |
| Melting point/range / Freezing point | : No data available |
| Boiling point/boiling range | : No data available |
| Vapor pressure | : 6.000 mmHg (7.9993 hpa) |
| Density | : 0.89 g/cm ³ |
| Water solubility | : Note: slightly soluble |
| Partition coefficient: n- octanol/water | : No data available |
| Viscosity, dynamic | : No data available |
| Viscosity, kinematic | : <20.5 mm ² /s at 104 °F (40 °C) |
| Relative vapor density | : No data available |
| Evaporation rate | : No data available |
| Burning rate | : No data available |
| Volatile organic compounds (VOC) content | : 325.4 g/l Less water and exempt solvent. |

10. Stability and reactivity

| | |
|---------------------------------------|---|
| Reactivity | : No dangerous reaction known under conditions of normal use. |
| Chemical stability | : The product is chemically stable. |
| Possibility of hazardous reactions | : Stable under recommended storage conditions. Vapors may form explosive mixture with air. |
| Conditions to avoid | : Heat, flames and sparks. |
| Incompatible materials | : No data available |

Lockstop Primer Adhesive

Revision Date 09/29/2016

Print Date 09/29/2016

11. Toxicological information

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization: Not classified based on available information.

Respiratory sensitization: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer if inhaled.

IARC Group 2B: Possibly carcinogenic to humans

| | | |
|------------|----------------|-----------|
| | Asphalt | 8052-42-4 |
| | ethylbenzene | 100-41-4 |
| NTP | Not applicable | |

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure in contact with skin.

May cause damage to organs through prolonged or repeated exposure if inhaled.

Reports have associated repeated and prolonged exposure to some of the chemicals in this product with permanent brain, liver, kidney and nervous system damage. Intentional misuse by deliberate concentration and inhalation of vapors may be harmful or fatal.

Aspiration toxicity

May be fatal if swallowed and enters airways.

12. Ecological information

| | |
|-------------------|--|
| Other information | Do not empty into drains; dispose of this material and its container in a safe way. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. |
|-------------------|--|

13. Disposal considerations**Disposal methods**

Waste from residues : Disposal of this product, solutions and any by-products should



at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

| | |
|--------------------------|-----------|
| UN number | 1133 |
| Description of the goods | Adhesives |
| Class | 3 |
| Packing group | III |
| Labels | 3 |
| Emergency Response | 128 |
| Guidebook Number | |

IATA

| | |
|--|-----------|
| UN number | 1133 |
| Description of the goods | Adhesives |
| Class | 3 |
| Packing group | III |
| Labels | 3 |
| Packing instruction (cargo aircraft) | 366 |
| Packing instruction (passenger aircraft) | 355 |
| Packing instruction (passenger aircraft) | Y344 |

IMDG

| | |
|--------------------------|-----------|
| UN number | 1133 |
| Description of the goods | ADHESIVES |
| Class | 3 |
| Packing group | III |
| Labels | 3 |
| EmS Number 1 | F-E |
| EmS Number 2 | S-D |

| | |
|------------------|----|
| Marine pollutant | no |
|------------------|----|

DOT: For Limited Quantity exceptions reference 49 CFR 173.150 (b)

IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4

Special precautions for user

No data available

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

**15. Regulatory information**

TSCA list : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

EPCRA - Emergency Planning and Community Right-to-Know**CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

SARA304 Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard
Chronic Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

| | | |
|--------------|-----------|----------|
| xylene | 1330-20-7 | 1 - 10 % |
| ethylbenzene | 100-41-4 | 1 - 5 % |

Clean Air Act

Ozone-Depletion Potential This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

| | | |
|--------------|-----------|----------|
| xylene | 1330-20-7 | 1 - 10 % |
| ethylbenzene | 100-41-4 | 1 - 5 % |

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

California Prop 65 WARNING! This product contains a chemical known in the State of California to cause cancer.
WARNING: This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

16. Other information

Lockstop Primer Adhesive

Revision Date 09/29/2016

Print Date 09/29/2016

HMIS Classification

| | | |
|----------------------------|---|---|
| Health | * | 3 |
| Flammability | | 3 |
| Physical Hazard | | 0 |
| Personal Protection | | X |

Caution: HMIS® rating is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating is not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® rating is to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). Please note HMIS® attempts to convey full health warning information to all employees.

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 09/29/2016

Material number: 419270