

Distributed By:

UNITIS
CONTRACTOR SUPPLIES

San Diego: 1-858-332-2133
El Cajon: 1-619-270-7100
Buena Park: 1-714-522-0055
Corona: 1-951-231-9700
www.unitisonline.com



ALL PURPOSE

PAINTERS PREFERRED®

**Acrylic
Latex Caulk**



White Lightning® Painter's Preferred® is an economical general purpose acrylic latex caulk suitable for sealing interior/exterior cracks and joints. Ideal for use on doors, windows and trim. White Lightning® Painter's Preferred® seals cracks between drywall, wood, and glass.

- Easy Application
- Cured Sealant is Mold and Mildew Resistant




PAINTABLE



WATER
CLEANUP

PART #	UPC	Color	SIZE
W13000010	0-23275-30010-1	White	10 fl oz



WHITE

**WHITE
LIGHTNING®**

ALL PURPOSE

**PAINTER'S
PREFERRED®**

- Easy Application
- Cured Caulk is Mold and Mildew Resistant

**ACRYLIC
LATEX
CAULK**



PAINTABLE



WATER CLEANUP



Meets
ASTM C-834



**WHITE
LIGHTNING**®

ALL PURPOSE
Painter's Preferred®

Product Description:

White Lightning® Painter's Preferred® is an economical general purpose acrylic latex caulk suitable for sealing interior/exterior cracks and joints. Ideal for use on doors, windows and trim. White Lightning® Painter's Preferred® seals cracks between drywall, wood, and glass..

Physical Properties:

Type: Acrylic

Colors: White

Shelf Life: 24 Months

Flash Point: n/a (water based)

Flammability: n/a (water based)

Full Cure Time: 7 to 14 days at 75° F

Tack Free Time: 5-7 Minutes at 75° F

Application Temperature: above 40° F

Service Temperature: -30° F to 180° F

Vehicle: Water

Solids by Weight: 82% +/- .2%

Weight/Gallon: 13.71 lbs/gal

Painting: Paintable

Primers: Not required

Mildew Resistance: Good

Water Resistance: Good

Odor: Low

Shrinkage: Low/Moderate

Performance Data:

Joint Size: 1/8" x 1/8" to 1/2" x 1/4"

Freeze-Thaw Stability: Passes Through 5 Cycles

Shelf Life: 24 Months

Clean Up: Water, promptly clean tools and excess caulk with water or a damp cloth.

Flexibility: Good

Linear Coverage 10oz cartridge 24ft at 1/4" wide by 1/4" deep bead

Painting: A minimum of 2-4 hours dry time is required before painting with latex or oil based paint. Allow extra dry time during periods of high humidity and/or cool temperatures.

ASTM: Meets ASTM Specification C-834, Grade NF

Application:

1. Remove all existing caulk
2. Clean thoroughly to remove all loose material, grease, dirt, oil, wax, loose paint, dust and soap film.
3. Remove mold/mildew with bleach (4:1 mix, water to bleach), and detergent that does not contain ammonia. Rinse surfaces and allow to dry.

• 10oz cartridge

- Cut cartridge tip 45° angle.
- Load cartridge into caulk gun.
- Squeeze trigger to start flow of caulk and work caulk into joint.
- Smooth caulk with proper tool.

Clean Up:

Water; promptly clean tools and excess caulk with water or a damp cloth.

Cautions:

See MSDS

Limitations:

For best results, apply at temperatures above 40° F and allow 24 hours to cure before exposing to moisture. Do not apply to frozen or frost covered surfaces. Not for use below grade, on aquariums or for marine use below the water line

LIMITED WARRANTY:

If when applied according to label directions within one year from date of purchase this product fails to perform to your satisfaction, as your sole remedy we will replace the product at no cost or refund the original purchase price with proof of purchase. Labor or costs associated with labor not included. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER.

For more information please call or write:

White Lightning® Products | 101 Prospect Ave. NW | Cleveland, OH 44115
1-800-241-5295 Option 1 Customer Service | 1-800-241-5295 Option 2 Technical Service
www.wlcaulk.com

PAINTER'S PREFERRED